

Farbreize nach ISO/IEC 15775 (Offset) und von BAM-2005-Prüfvorlagen

Gerätefarben (d), siehe Namen in CIE R8-09 und ISO/IEC 15775	Offset-Druck (o) adaptierte (a) CIELAB-Daten					Muster der BAM-Prüfvorlagen adaptierte (a) CIELAB-Daten				
	L^*_{oa}	a^*_{oa}	b^*_{oa}	$C^*_{ab,oa}$	$h_{ab,oa}$	L^*_{da}	a^*_{da}	b^*_{da}	$C^*_{ab,da}$	$h_{ab,da}$
$C=C_d$ Cyanblau (Cyan)	58.62	-30.35	-45.02	54.3	236	58.09	-34.15	-47.14	58.21	234
$M=M_d$ Magentarot (Magenta)	48.13	75.27	-8.37	75.73	353	46.88	73.07	-10.95	73.89	351
$Y=Y_d$ Gelb	90.37	-10.27	91.74	92.32	96	88.56	-5.97	90.19	90.39	93
$O=R_d$ Orangerot (Rot)	47.94	65.38	50.51	82.62	37	50.78	64.52	51.26	82.4	38
$L=G_d$ Laubgrün (Grün)	50.9	-62.83	34.95	71.89	150	49.24	-62.06	35.27	71.38	150
$V=B_d$ Violettblau (Blau)	25.72	30.99	-44.41	54.16	304	28.18	28.97	-43.27	52.08	303
W Wei 8	95.41	0.0	0.0	0.0	0	94.5	0.0	0.0	0.0	0
N Schwarz	18.01	0.0	0.0	0.0	0	19.14	0.0	0.0	0.0	0

Quelle: Kittelmann (2005), Diplomarbeit, TU Berlin