

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für A00, Y_N=3,6, Y_W=90, Y_m=520 770

l ₁	λ ₁	l ₂	λ ₂	Y	A ₁	B ₁	C _{AB1}	A ₁	B ₁	C _{AB1}	a ₁	b ₁	h _{xy1}	l _d	λ _d	l _c	λ _c	Code
1	405	34	574	45.93	-59.57	-12.24	60.82	0.3094	-0.2489	191.6	18 494	39 599	Cm					
6	435	34	574	46.09	-60.23	-8.5	60.83	0.3056	-0.2161	188.0	19 496	42 612	612					
9	450	34	574	46.35	-60.24	-2.79	61.11	0.3015	-0.1664	182.6	20 501	-1 501e						
12	460	35	575	46.0	-61.33	3.74	61.44	0.295	-0.1097	176.5	21 508	-1 508e						
13	465	35	575	46.26	-61.2	5.94	61.49	0.2991	-0.0909	174.2	22 512	-1 512e						
13	470	35	576	46.86	-61.21	6.51	61.51	0.3058	-0.0897	174.2	22 513	-1 513e						
14	475	35	577	47.65	-60.91	8.27	61.47	0.3169	-0.0727	172.2	23 519	-1 519e	Gm					
16	480	35	579	48.7	-59.74	11.48	60.83	0.3376	-0.0479	169.1	26 533	-1 533e						
17	485	36	582	50.33	-58.25	13.07	59.7	0.3653	-0.0383	167.3	28 540	-1 540e						
18	490	37	588	53.85	-54.96	15.14	57.01	0.42	-0.0228	165.5	29 548	-1 548e						
19	495	40	601	61.06	-44.1	18.35	47.76	0.5394	-0.022	157.4	31 559	-1 559e						
20	500	-1 500e	77.63	5.72	24.77	25.42	48.578	-0.0146	76.9	35 576	13 469	max						
21	510	-1 509e	76.57	8.29	24.82	26.17	48.716	-0.0126	71.5	35 576	14 472							
24	520	-1 520e	71.52	19.47	23.77	30.73	0.9372	-0.0093	50.6	35 579	16 480	Ym						
26	530	-1 530e	66.62	28.9	22.27	36.49	1.0018	-0.0085	37.6	36 582	16 484							
28	540	-1 540e	60.72	38.73	20.3	43.73	1.0834	-0.0085	27.6	37 585	17 487							
28	545	-1 544e	60.72	38.73	20.3	43.73	1.0834	-0.0085	27.6	37 585	17 487							
29	550	-1 549e	57.48	43.44	19.18	47.49	1.1306	-0.0087	23.8	37 586	17 489							
31	555	-1 555e	50.54	51.76	16.76	54.41	1.2379	-0.0096	17.9	38 590	18 491							
32	560	-1 560e	46.93	55.05	15.48	57.19	1.2975	-0.0102	15.7	38 593	18 492							
34	574	1 405	44.06	59.57	12.24	60.81	1.369	-0.0311	11.6	39 599	18 494	Rm						
34	574	6 435	43.9	60.23	8.5	60.83	1.3771	-0.0647	8.0	42 612	19 496							
34	574	9 450	43.64	61.04	2.79	61.1	1.3877	-0.1166	2.6	-1 501e	20 501							
35	575	12 460	43.99	61.32	-3.74	61.44	1.3858	-0.1763	356.5	-1 508e	21 508							
35	575	13 465	43.73	61.19	-5.94	61.48	1.388	-0.1966	354.4	-1 512e	22 512							
35	576	13 470	43.13	61.2	-6.15	61.5	1.3958	-0.1993	354.2	-1 513e	22 513							
35	577	14 475	42.34	60.9	-8.27	61.46	1.4036	-0.2204	352.2	-1 519e	23 519	Mm						
35	579	16 480	41.29	59.73	-11.48	60.82	1.4069	-0.2535	349.1	-1 533e	26 533							
36	582	17 485	39.66	58.24	-13.07	59.69	1.4155	-0.2741	347.3	-1 540e	28 540							
37	588	18 490	36.14	54.95	-15.13	57.0	1.4364	-0.3098	344.5	-1 548e	29 548							
40	601	19 495	28.93	44.09	-18.34	47.75	1.4379	-0.3959	337.4	-1 559e	31 559							
-1	500e	20 500	12.36	-5.72	-24.76	25.41	60.631	-0.9436	256.9	13 469	35 576	min						
-1	509e	21 510	13.42	-8.29	-24.81	26.16	58.81	-0.8819	251.5	14 472	35 576							
-1	520e	24 520	18.47	-19.47	-23.77	30.72	0.4067	-0.6569	230.6	16 480	35 579	Bm						
-1	530e	26 530	23.37	-28.9	-22.27	36.49	0.3337	-0.5233	217.6	16 484	36 582							
-1	540e	28 540	29.27	-38.72	-20.3	43.72	0.299	-0.4197	207.6	17 487	37 585							
-1	544e	28 545	29.27	-38.72	-20.3	43.72	0.299	-0.4197	207.6	17 487	37 585							
-1	549e	29 550	32.51	-43.44	-19.18	47.49	0.2938	-0.3783	203.8	17 489	37 586							
-1	555e	31 555	39.45	-51.76	-16.76	54.41	0.3034	-0.3122	197.9	18 491	38 590							
-1	560e	32 560	43.06	-55.06	-15.48	57.19	0.3169	-0.2861	195.7	18 492	38 593							
W0	380	770	89.99	0.0	0.0	0.0	0.8283	-0.1422	0.0	B _c =1,000								
N0	380	770	3.59	0.0	0.0	0.0	0.8283	-0.1422	0.0	x _c =0,110								

Technische Information: <http://farbe.li-tu-berlin.de> oder <http://color.li-tu-berlin.de>

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für A00, Y_N=3,6, Y_W=90, Y_m=520 770

l ₁	λ ₁	l ₂	λ ₂	Y	A ₂	B ₂	C _{AB2}	a ₂	b ₂	h _{xy2}	l _d	λ _d	l _c	λ _c	Code
1	405	34	574	45.93	-59.57	-30.6	66.98	0.3094	-0.2489	207.1	18 494	39 599	Cm		
6	435	34	574	46.09	-60.23	-21.26	63.88	0.3056	-0.2161	199.4	19 496	42 612	612		
9	450	34	574	46.35	-61.04	-6.98	61.44	0.3015	-0.1664	186.5	20 501	-1 501e			
12	460	35	575	46.0	-61.33	9.36	62.04	0.295	-0.1097	171.3	21 508	-1 508e			
13	465	35	575	46.26	-61.2	14.85	62.98	0.2991	-0.0909	166.3	22 512	-1 512e			
13	470	35	576	46.86	-61.21	15.38	63.11	0.3058	-0.0897	163.8	22 513	-1 513e			
14	475	35	577	47.65	-60.91	20.69	64.33	0.3169	-0.0727	161.2	23 519	-1 519e	Gm		
16	480	35	579	48.7	-59.74	28.71	66.28	0.3376	-0.0479	154.3	26 533	-1 533e			
17	485	36	582	50.33	-58.25	32.69	66.8	0.3653	-0.0383	150.6	28 540	-1 540e			
18	490	37	588	53.85	-54.96	37.85	66.73	0.42	-0.0298	145.4	29 548	-1 548e			
19	495	40	601	61.06	-44.1	45.87	63.63	0.5394	-0.022	133.8	31 559	-1 559e			
20	500	-1 500e	77.63	5.72	61.93	62.19	65.78	0.19	85.78	-0.0146	84.7	35 576	13 469	max	
21	510	-1 509e	76.57	8.29	62.05	62.61	66.19	0.8716	-0.0126	82.3	35 576	14 472			
24	520	-1 520e	71.52	19.47	59.43	62.54	69.372	-0.0093	71.8	35 579	16 480	Ym			
26	530	-1 530e	66.62	28.9	55.68	62.74	1.0018	-0.0085	62.5	36 582	16 484				
28	540	-1 540e	60.72	38.73	50.76	63.85	1.0834	-0.0085	52.6	37 585	17 487				
28	545	-1 544e	60.72	38.73	50.76	63.85	1.0834	-0.0085	52.6	37 585	17 487				
29	550	-1 549e	57.48	43.44	47.97	64.72	1.1306	-0.0087	47.8	37 586	17 489				
31	555	-1 555e	50.54	51.76	41.9	66.6	1.2379	-0.0096	38.9	38 590	18 491				
32	560	-1 560e	46.93	55.05	38.72	67.31	1.2975	-0.0102	35.1	38 593	18 492				
34	574	1 405	44.06	59.57	30.6	66.97	1.369	-0.0311	27.1	39 599	18 494	Rm			
34	574	6 435	43.9	60.23	21.26	63.87	1.3771	-0.0647	19.4	42 612	19 496				
34	574	9 450	43.64	61.04	6.98	61.43	1.3877	-0.1166	6.5	-1 501e	20 501				
35	575	12 460	43.99	61.32	-9.36	62.03	1.3858	-0.1763	351.3	-1 508e	21 508				
35	575	13 465	43.73	61.19	-14.85	62.97	1.388	-0.1966	346.3	-1 512e	22 512				
35	576	13 470	43.13	61.2	-15.38	63.1	1.3958	-0.1993	345.8	-1 513e	22 513				
35	577	14 475	42.34	60.9	-18.29	63.61	1.4036	-0.2204	341.2	-1 519e	23 519	Mm			
35	579	16 480	41.29	59.73	-28.71	66.27	1.4069	-0.2535	334.3	-1 533e	26 533				
36	582	17 485	39.66	58.24	-32.69	66.78	1.4155	-0.2741	330.6	-1 540e	28 540				
37	588	18 490	36.14	54.95	-37.84	66.72	1.4364	-0.3098	325.4	-1 548e	29 548				
40	601	19 495	28.93	44.09	-45.86	63.62	1.4379	-0.3959	313.8	-1 559e	31 559				
-1	500e	20 500	12.36	-5.72	-61.91	62.17	60.6431	-0.9436	264.2	13 469	35 576	min			
-1	509e	21 510	13.42	-8.29	-62.04	62.59	58.81	-0.8819	262.3	14 472	35 576				
-1	520e	24 520	18.47	-19.47	-59.43	63.53	0.4067	-0.6569	251.8	16 480	35 579	Bm			
-1	530e	26 530	23.37	-28.9	-55.68	62.73	0.3337	-0.5233	242.5	16 484	36 582				
-1	540e	28 540	29.27	-38.72	-50.76	63.85	0.299	-0.4197	232.6	17 487	37 585				
-1	544e	28 545	29.27	-38.72	-50.76	63.85	0.299	-0.4197	232.6	17 487	37 585				
-1	549e	29 550	32.51	-43.44	-47.97	64.72	0.2938	-0.3783	227.8	17 489	37 586				
-1	555e	31 555	39.45	-51.76	-41.9	66.6	0.3034	-0.3122	218.9	18 491	38 590				
-1	560e	32 560	43.06	-55.06	-38.72	67.31	0.3169	-0.2861	215.1	18 492	38 593				
W0	380	770	89.99	0.0	0.0	0.0	0.8283	-0.3557	0.0	B _c =2,500					
N0	380	770	3.59	0.0	0.0	0.0	0.8283	-0.3557	0.0	x _c =0,110					

TUB-Registrierung: 20230701-egh8/egh810n1.txt /ps
 Anwendung für Beurteilung und Messung von Display- oder Druck-Ausgabe