

9stufige Grauskalierung zwischen $L^*_{0aN}=17.9$ und $L^*_{0aW}=95.9$, $Y_{0ref}=0.4$, Normierung Grau U

$L^*_{0aN}=17.9$, $L^*_{0aU}=56.9$, $L^*_{0aW}=96.0$, $Y_{0aN}=2.5$, $Y_{0aU}=24.9$, $Y_{0aW}=90.0$, $C_{0aY}=Y_{0aW}:Y_{0aN}=36.0$

$L^*_{taN}=19.4$, $L^*_{taU}=57.0$, $L^*_{taW}=95.6$, $Y_{taN}=2.8$, $Y_{taU}=24.9$, $Y_{taW}=89.0$, $C_{taY}=Y_{taW}:Y_{taN}=31.2$

Regularitätsindex nach ISO/IEC 15775:2022, Anhang G für 5 und 9 Stufen

$g^* = 100 [\Delta L^*_{min}] / [\Delta L^*_{max}]$, $L^*_{CIELAB} = 116 [Y/Y_n]^{1/3} - 16$ mit $Y \geq 0,882$, $Y_n=100$

$g^*_5=99$, $g^*_9=99$

$g^*_5=95$, $g^*_9=93$

$g^*_5=99$, $g^*_9=98$

L^*_{CIELAB}	n0. i	angestrebte Ausgabe				reale Ausgabe					linearisierte Ausgabe	
		L^*_{0a}	L^*_{0r}	Y_{0a}	Y_{0r}	L^*_{ta}	ΔL^*_{ta}	L^*_{tr}	Y_{ta}	$(L^*_{tr})^{1/1.02}$	L^*_{la}	ΔL^*_{la}
100	○ 9	96.0	1.0	90.0	1.0	95.6		1.0	89.0	1.0	95.6	
	● 8	86.2	0.875	68.5	0.754	85.9	9.7	0.873	67.8	0.875	86.1	9.5
	● 7	76.5	0.75	50.7	0.55	76.2	9.7	0.746	50.3	0.75	76.6	9.5
75	● 6	66.7	0.625	36.3	0.386	66.6	9.6	0.619	36.1	0.625	67.0	9.5
	● 5	56.9	0.5	24.9	0.256	57.0	9.6	0.493	24.9	0.5	57.5	9.5
50	● 4	47.2	0.375	16.2	0.156	47.4	9.6	0.367	16.3	0.374	47.9	9.5
	● 3	37.4	0.25	9.8	0.083	37.9	9.5	0.242	10.0	0.249	38.4	9.5
	● 2	27.7	0.125	5.3	0.032	28.5	9.4	0.119	5.6	0.124	28.9	9.5
25	● 1	17.9	0.0	2.5	0.0	19.4	9.0	0.0	2.8	0.0	19.4	9.4
0												

$\Delta L^*_{0a}=9.7$

(i=1,2,...,8)

Normierung: $Y_{taiU}=Y_{0aU} \frac{Y_{0ai}+Y_{0ref}}{Y_{0aU}+Y_{0ref}}$