


<http://farbe.li.tu-berlin.de/fei1/fei110np.pdf/.ps>; only vector graphic VG; start output
see separate images of this page: <http://farbe.li.tu-berlin.de/fei1/fei1.htm>

see similar files of the whole series: <http://farbe.li.tu-berlin.de/feis.htm>
technical information: <http://farbe.li.tu-berlin.de/A/33872E.html>
or <http://standards.iso.org/iso/9241/306/ed-2/index.html>



TUB registration: 20240301-fei1/fei110np.pdf/.ps
application for evaluation and measurement of display or print output
TUB material: code=rh4ta

fei10-7n-030-0: Test chart 2o with 40x27=1080 colours; digital equidistant 9 or 16 step colour scales; Colour data in column (A-n): $rgb / cmy0 (A_j + k26_{n27}), 000n (k), w (l), nnn0 (m), www (n), colorml = 0$

TUB-test chart fei1; Test chart 2o_d0 with 40x27=1080 colours; DH
Digital equidistant 9 or 16 step colour scales

000n/w/cmy0/rgb
->rgb*_d, 030-0:



<http://farbe.li.tu-berlin.de/fei1/fei110np.pdf/.ps>; only vector graphic VG; start output
 see separate images of this page: <http://farbe.li.tu-berlin.de/fei1/fei1.htm>

see similar files of the whole series: <http://farbe.li.tu-berlin.de/feis.htm>
 technical information: <http://farbe.li.tu-berlin.de/A/33872E.html>
 or <http://standards.iso.org/iso/9241/306/ed-2/index.html>

TUB registration: 20240301-fei1/fei110np.pdf/.ps
 application for evaluation and measurement of display or print output
 TUB material: code=rhatha


i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE^*	Start output S1
1	0.0	0.0	0.0	0.0	0.0	0.01
2	6.36	0.0	0.0	0.0	0.0	0.01
3	12.72	0.0	0.13	0.0	0.0	0.01
4	19.08	0.0	0.2	0.0	0.0	0.01
5	25.44	0.0	0.27	0.0	0.0	0.01
6	31.8	0.0	0.33	0.0	0.0	0.01
7	38.16	0.0	0.4	0.0	0.0	0.01
8	44.52	0.0	0.47	0.0	0.0	0.01
9	50.89	0.0	0.53	0.0	0.0	0.01
10	57.25	0.0	0.6	0.0	0.0	0.01
11	63.61	0.0	0.67	0.0	0.0	0.01
12	69.97	0.0	0.73	0.0	0.0	0.01
13	76.33	0.0	0.8	0.0	0.0	0.01
14	82.69	0.0	0.87	0.0	0.0	0.01
15	89.05	0.0	0.93	0.0	0.0	0.01
16	95.41	0.0	1.0	0.0	0.0	0.01
17	0.0	0.0	0.0	0.0	0.0	0.01
18	23.85	0.0	0.25	0.0	0.0	0.01
19	47.71	0.0	0.5	0.0	0.0	0.01
20	71.56	0.0	0.75	0.0	0.0	0.01
21	95.41	0.0	1.0	0.0	0.0	0.01

Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G

Mean lightness difference (16 steps)
 $\Delta E^*_{CIELAB} = 0.0$

Mean lightness difference (5 steps)
 $\Delta L^*_{CIELAB} = 0.0$

Mean colour reproduction index: $R^*_{ab,m} = 100$



fei10-3n-030-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

fei11-3n-030-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y^*_{intended}$ (absolute)	0.0/0.0	6.3/0.7	12.7/1.5	19.0/2.7	25.4/4.5	31.8/6.9	38.1/10.1	44.5/14.2	50.8/19.1	57.2/25.1	63.6/32.3	69.9/40.7	76.3/50.4	82.6/61.5	89.0/74.2	95.4/88.5
$w^* w^* w^*$ setrgb																
gp=1.00																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = L^*_{CIELAB,r}$ (relative)																
$w^*_{intended}$	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0,0	0,067	0,133	0,2	0,267	0,333	0,4	0,467	0,533	0,6	0,667	0,733	0,8	0,867	0,933	1,0

OE740-7n, Picture A7-030-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

TUB-test chart fei1; In-output relation according to ISO 9241-306; DH
 Viewing Y contrast $Y_W:Y_N=88,9:0,31$; Y_N range 0,0 to <0,46

000n/w/cmy0/rgb
 ->rgb*_d, 030-2: