

i	LAB*ref		l*out		LAB*out		LAB*out/c-ref		$\Delta E^*$	<b>Start-Ausgabe S1</b>	
1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	<b>Kennzeichnung nach</b>	
2	6.36	0.0	0.0	0.07	6.36	0.0	0.0	0.0	0.01	<b>ISO/IEC 15775 Anhang G</b>	
3	12.72	0.0	0.0	0.13	12.72	0.0	0.0	0.0	0.01	<b>und DIN 33866-1 Anhang G</b>	
4	19.08	0.0	0.0	0.2	19.08	0.0	0.0	0.0	0.01		
5	25.44	0.0	0.0	0.27	25.44	0.0	0.0	0.0	0.01		
6	31.8	0.0	0.0	0.33	31.8	0.0	0.0	0.0	0.01		
7	38.16	0.0	0.0	0.4	38.16	0.0	0.0	0.0	0.01		
8	44.52	0.0	0.0	0.47	44.52	0.0	0.0	0.0	0.01		
9	50.89	0.0	0.0	0.53	50.89	0.0	0.0	0.0	0.01		
10	57.25	0.0	0.0	0.6	57.25	0.0	0.0	0.0	0.01		
11	63.61	0.0	0.0	0.67	63.61	0.0	0.0	0.0	0.01		
12	69.97	0.0	0.0	0.73	69.97	0.0	0.0	0.0	0.01		
13	76.33	0.0	0.0	0.8	76.33	0.0	0.0	0.0	0.01		
14	82.69	0.0	0.0	0.87	82.69	0.0	0.0	0.0	0.01		
15	89.05	0.0	0.0	0.93	89.05	0.0	0.0	0.0	0.01	<b>Mittlerer Helligkeitsabstand (16 Stufen)</b>	
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.01	$\Delta E^*_{\text{CIELAB}} = 0.0$	
17	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01		
18	23.85	0.0	0.0	0.25	23.85	0.0	0.0	0.0	0.01		
19	47.71	0.0	0.0	0.5	47.71	0.0	0.0	0.0	0.01		
20	71.56	0.0	0.0	0.75	71.56	0.0	0.0	0.0	0.01	<b>Mittlerer Helligkeitsabstand (5 Stufen)</b>	
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.01	$\Delta L^*_{\text{CIELAB}} = 0.0$	
<b>Mittlerer Farbwiedergabe-Index:</b>								$R^*_{\text{ab,m}} = 100$			