

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für P60, $Y_N=0$, $Y_W=90$, $Y_m=520_770$												
i_1, λ_1	i_2, λ_2	Y	A	B	C_{AB}	a	b	h_{xy}	i_d, λ_d	i_c, λ_c	Code	
0	405	32 563	53.56	-50.83	-37.27	63.03	0.5907	-0.6965	216.2	16 483 38 590	Cm	
6	435	32 563	54.12	-60.57	-18.04	63.2	0.5227	-0.5515	196.5	17 487 44 621		
10	450	33 565	54.2	-74.1	11.55	74.99	0.4236	-0.3329	171.1	19 497 -1 497c		
11	460	33 566	55.45	-77.42	20.13	79.99	0.4119	-0.2729	165.4	20 502 -1 502c		
13	465	33 568	56.12	-81.71	33.7	88.38	0.388	-0.1779	157.5	22 513 -1 513c		
14	470	34 570	57.09	-83.01	39.7	92.02	0.3888	-0.1399	154.4	24 521 -1 521c	Gm	
15	475	34 574	59.7	-83.37	46.41	95.41	0.4118	-0.1072	150.8	25 529 -1 529c		
15	480	36 580	63.87	-82.5	50.76	96.86	0.4537	-0.1002	148.3	27 535 -1 535c		
17	485	39 595	70.8	-72.25	63.39	96.12	0.5622	-0.06	138.7	29 549 -1 549c		
18	490	-1 490c	85.0	-25.38	79.98	83.91	0.8509	-0.0418	107.6	33 566 11 459	max	
19	495	-1 495c	83.76	-22.46	80.01	83.11	0.8631	-0.036	105.6	33 567 12 461		
20	500	-1 500c	82.2	-18.71	79.42	81.59	0.8793	-0.0316	103.2	33 568 12 464		
22	510	-1 510c	77.89	-8.53	76.28	76.76	0.9265	-0.0264	96.3	34 570 13 469		
24	520	-1 520c	71.91	4.55	70.72	70.87	0.9957	-0.0247	86.3	34 572 14 473	Ym	
25	530	-1 529c	68.43	11.56	67.29	68.27	1.038	-0.0248	80.2	34 574 15 475		
27	540	-1 539c	60.8	25.33	59.57	64.73	1.137	-0.0262	66.9	35 578 15 478		
29	545	-1 545c	52.69	37.52	51.21	63.48	1.2552	-0.0294	53.7	36 582 16 480		
29	550	-1 549c	52.69	37.52	51.21	63.48	1.2552	-0.0294	53.7	36 582 16 480		
30	555	-1 554c	48.59	42.61	46.95	63.4	1.3211	-0.0316	47.7	36 584 16 481		
32	560	-1 560c	40.5	50.12	38.52	63.21	1.4654	-0.0376	37.5	37 589 16 483		
32	563	0 405	46.43	50.84	37.27	63.04	1.4083	-0.097	36.2	38 590 16 483	Rm	
32	563	6 435	45.87	60.57	18.04	63.2	1.4985	-0.2608	16.5	44 621 17 487		
33	565	10 450	45.79	74.08	-11.55	74.98	1.6175	-0.519	351.1	-1 497c 19 497		
33	566	11 460	44.54	77.4	-20.13	79.98	1.6655	-0.5989	345.4	-1 502c 20 502		
33	568	13 465	43.87	81.68	-33.69	88.36	1.7151	-0.7253	337.5	-1 513c 22 513		
34	570	14 470	42.9	82.98	-39.69	91.99	1.7441	-0.7882	334.4	-1 521c 24 521	Mm	
34	574	15 475	40.29	83.34	-46.39	95.38	1.7977	-0.8786	330.8	-1 529c 25 529		
36	580	15 480	36.12	82.47	-50.74	96.83	1.8835	-0.9799	328.3	-1 535c 27 535		
39	595	17 485	29.19	72.22	-63.36	96.08	1.9601	-1.2864	318.7	-1 549c 29 549		
-1	490c	18 490	14.99	25.36	-79.92	83.85	1.6471	-2.5507	287.6	11 459 33 566	min	
-1	495c	19 495	16.23	22.44	-79.96	83.05	1.5234	-2.3881	285.6	12 461 33 567		
-1	500c	20 500	17.79	18.7	-79.37	81.54	1.3907	-2.2019	283.2	12 464 33 568		
-1	510c	22 510	22.1	8.53	-76.24	76.72	1.1247	-1.7979	276.3	13 469 34 570		
-1	520c	24 520	28.08	-4.55	-70.7	70.84	0.9055	-1.4253	266.3	14 473 34 572	Bm	
-1	529c	25 530	31.56	-11.56	-67.27	68.25	0.8238	-1.2706	260.2	15 475 34 574		
-1	539c	27 540	39.19	-25.32	-59.55	64.72	0.7119	-1.0259	246.9	15 478 35 578		
-1	545c	29 545	47.3	-37.51	-51.2	63.47	0.6531	-0.8511	233.7	16 480 36 582		
-1	549c	29 550	47.3	-37.51	-51.2	63.47	0.6531	-0.8511	233.7	16 480 36 582		
-1	554c	30 555	51.4	-42.6	-46.94	63.4	0.6388	-0.7834	227.7	16 481 36 584		
-1	560c	32 560	59.49	-50.11	-38.52	63.21	0.6334	-0.6771	217.5	16 483 37 589		
W0	380	770	89.99	0.0	0.0	0.0	0.9704	-0.4181	0.0	$B_c=1,000$		
N0	380	770	3.59	0.0	0.0	0.0	0.9704	-0.4181	0.0	$x_c=0,000$		

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für P55, $Y_N=0$, $Y_W=90$, $Y_m=520_770$												
i_1, λ_1	i_2, λ_2	Y	A	B	C_{AB}	a	b	h_{xy}	i_d, λ_d	i_c, λ_c	Code	
1	405	32 564	53.53	-53.38	-33.72	63.14	0.5754	-0.6358	212.2	16 484	38 591	Cm
6	435	32 564	54.05	-61.78	-17.18	64.13	0.517	-0.511	195.5	17 488	44 620	
9	450	33 565	54.21	-71.06	2.96	71.13	0.4499	-0.3619	177.6	18 494	-1 494c	
11	460	33 567	55.19	-76.92	17.46	78.87	0.4168	-0.2572	167.2	20 502	-1 502c	
13	465	33 568	55.8	-80.9	29.99	86.28	0.3943	-0.1688	159.6	22 513	-1 513c	
14	470	34 570	56.61	-82.0	35.44	89.33	0.3949	-0.1334	156.6	24 520	-1 520c	Gm
15	475	34 574	58.99	-82.35	41.46	92.2	0.4159	-0.1026	153.2	25 529	-1 529c	
16	480	36 580	62.08	-81.09	47.31	93.88	0.4517	-0.0789	149.7	27 536	-1 536c	
17	485	38 592	68.99	-73.25	56.13	92.28	0.5496	-0.0583	142.5	29 547	-1 547c	
17	490	-1 489c	86.27	-24.86	72.7	76.83	0.859	-0.0467	108.8	33 566	11 456	max
19	495	-1 495c	84.12	-19.97	73.59	76.26	0.8793	-0.0338	105.1	33 567	12 462	
19	500	-1 499c	84.12	-19.97	73.59	76.26	0.8793	-0.0338	105.1	33 567	12 462	
21	510	-1 509c	80.75	-11.84	72.11	73.08	0.9155	-0.0265	99.3	33 569	13 467	
24	520	-1 520c	72.63	6.34	65.55	65.86	1.0092	-0.0228	84.4	34 573	14 474	Ym
26	530	-1 530c	65.55	20.16	59.11	62.45	1.0973	-0.0231	71.1	35 576	15 477	
27	540	-1 539c	61.69	26.89	55.51	61.69	1.1486	-0.0238	64.1	35 578	15 479	
28	545	-1 544c	57.71	33.25	51.76	61.52	1.2047	-0.025	57.2	36 580	16 480	
30	550	-1 550c	49.55	44.19	44.01	62.37	1.3309	-0.0285	44.8	37 585	16 482	
30	555	-1 554c	49.55	44.19	44.01	62.37	1.3309	-0.0285	44.8	37 585	16 482	
32	560	-1 560c	41.43	51.79	36.25	63.22	1.4742	-0.0338	34.9	38 590	16 484	
32	564	1 405	46.46	53.39	33.72	63.15	1.4339	-0.0934	32.2	38 591	16 484	Rm
32	564	6 435	45.94	61.78	17.18	64.13	1.5122	-0.2341	15.5	44 620	17 488	
33	565	9 450	45.78	71.06	-2.96	71.12	1.5951	-0.4097	357.6	-1 494c	18 494	
33	567	11 460	44.8	76.9	-17.46	78.86	1.6609	-0.5397	347.2	-1 502c	20 502	
33	568	13 465	44.19	80.88	-29.98	86.26	1.7063	-0.6552	339.6	-1 513c	22 513	
34	570	14 470	43.38	81.98	-35.43	89.31	1.7302	-0.7105	336.6	-1 520c	24 520	Mm
34	574	15 475	41.0	82.33	-41.45	92.17	1.7775	-0.7882	333.2	-1 529c	25 529	
36	580	16 480	37.91	81.06	-47.29	93.85	1.8294	-0.8827	329.7	-1 536c	27 536	
38	592	17 485	31.0	73.22	-56.11	92.25	1.9189	-1.1077	322.5	-1 547c	29 547	
-1	489c	17 490	13.72	24.84	-72.65	76.78	1.6982	-2.5011	288.8	11 456	33 566	min
-1	495c	19 495	15.87	19.95	-73.55	76.21	1.4773	-2.2375	285.1	12 462	33 567	
-1	499c	19 500	15.87	19.95	-73.55	76.21	1.4773	-2.2375	285.1	12 462	33 567	
-1	509c	21 510	19.24	11.84	-72.08	73.04	1.2204	-1.8818	279.3	13 467	33 569	
-1	520c	24 520	27.36	-6.34	-65.53	65.84	0.8815	-1.3419	264.4	14 474	34 573	Bm
-1	530c	26 530	34.44	-20.16	-59.1	62.44	0.7401	-1.0701	251.1	15 477	35 576	
-1	539c	27 540	38.3	-26.88	-55.5	61.67	0.6934	-0.9635	244.1	15 479	35 578	
-1	544c	28 545	42.28	-33.24	-51.75	61.51	0.6598	-0.8734	237.2	16 480	36 580	
-1	550c	30 550	50.44	-44.18	-44.0	62.36	0.6239	-0.7327	224.8	16 482	37 585	
-1	554c	30 555	50.44	-44.18	-44.0	62.36	0.6239	-0.7327	224.8	16 482	37 585	
-1	560c	32 560	58.56	-51.79	-36.25	63.22	0.6205	-0.6314	214.9	16 484	38 590	
W0	380	770	90.0	0.0	0.0	0.0	0.9742	-0.3838	0.0	$B_c=1,000$		
N0	380	770	3.6	0.0	0.0	0.0	0.9742	-0.3838	0.0	$x_c=0,000$		

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für P50, $Y_N=0$, $Y_W=90$, $Y_m=520_770$												
i_1, λ_1	i_2, λ_2	Y	A	B	C_{AB}	a	b	h_{xy}	i_d, λ_d	i_c, λ_c	Code	
0	405	33 565	52.86	-55.33	-31.51	63.67	0.5622	-0.5843	209.6	17 485	38 592	Cm
7	435	33 565	53.24	-65.38	-11.15	66.33	0.4897	-0.4296	189.6	18 490	-1 490c	
9	450	33 566	54.01	-71.22	1.64	71.24	0.4534	-0.3337	178.6	19 495	-1 495c	
11	460	33 568	54.89	-76.51	14.64	77.9	0.4233	-0.2392	169.1	20 502	-1 502c	
12	465	33 569	55.73	-78.85	21.13	81.63	0.415	-0.1942	164.9	21 507	-1 507c	
14	470	34 571	56.07	-81.01	30.87	86.69	0.4031	-0.1257	159.1	24 520	-1 520c	Gm
15	475	34 574	58.2	-81.36	36.17	89.04	0.4218	-0.0973	156.0	25 528	-1 528c	
16	480	35 579	61.34	-80.11	41.57	90.25	0.4585	-0.0748	152.5	27 536	-1 536c	
16	485	37 589	67.88	-75.48	47.21	89.03	0.5361	-0.0676	147.9	28 544	-1 544c	
17	490	47 636	83.91	-33.01	63.13	71.24	0.8235	-0.0449	117.6	33 565	-1 565c	
19	495	-1 495c	84.54	-17.25	66.46	68.66	0.8993	-0.0314	104.5	33 568	12 462	max
20	500	-1 500c	83.11	-13.78	66.17	67.59	0.9146	-0.0274	101.7	33 569	13 465	
21	510	-1 509c	81.32	-9.44	65.35	66.03	0.9344	-0.0244	98.2	34 570	13 468	
24	520	-1 520c	73.48	8.26	59.75	60.32	1.0259	-0.0206	82.1	34 574	14 474	Ym
26	530	-1 530c	66.55	21.88	54.11	58.37	1.1124	-0.0207	67.9	35 577	15 478	
28	540	-1 540c	58.82	34.91	47.59	59.03	1.2183	-0.0222	53.7	36 581	16 481	
28	545	-1 544c	58.82	34.91	47.59	59.03	1.2183	-0.0222	53.7	36 581	16 481	
30	550	-1 550c	50.71	45.92	40.65	61.33	1.3431	-0.0252	41.5	37 585	16 483	
30	555	-1 554c	50.71	45.92	40.65	61.33	1.3431	-0.0252	41.5	37 585	16 483	
32	560	-1 560c	42.57	53.68	33.65	63.35	1.4852	-0.0297	32.0	38 590	17 485	
33	565	0 405	47.13	55.33	31.51	63.68	1.4505	-0.0784	29.6	38 592	17 485	Rm
33	565	7 435	46.75	65.38	11.15	66.32	1.5403	-0.2504	9.6	-1 490c	18 490	
33	566	9 450	45.98	71.21	-1.64	71.23	1.6004	-0.3601	358.6	-1 495c	19 495	
33	568	11 460	45.1	76.5	-14.63	77.89	1.6594	-0.4757	349.1	-1 502c	20 502	
33	569	12 465	44.26	78.83	-21.12	81.62	1.6934	-0.5368	344.9	-1 507c	21 507	
34	571	14 470	43.92	80.99	-30.86	86.67	1.7185	-0.6269	339.1	-1 520c	24 520	Mm
34	574	15 475	41.79	81.33	-36.16	89.01	1.7594	-0.692	336.0	-1 528c	25 528	
35	579	16 480	38.65	80.08	-41.55	90.22	1.8096	-0.7759	332.5	-1 536c	27 536	
37	589	16 485	32.11	75.45	-47.2	89.0	1.9206	-0.9337	327.9	-1 544c	28 544	
47	636	17 490	16.08	32.99	-63.09	71.2	1.8015	-1.9149	297.6	-1 565c	33 565	
-1	495c	19 495	15.45	17.24	-66.42	68.62	1.4272	-2.0652	284.5	12 462	33 568	min
-1	500c	20 500	16.88	13.77	-66.14	67.55	1.3073	-1.9129	281.7	13 465	33 569	
-1	509c	21 510	18.67	9.44	-65.32	66.0	1.1831	-1.7449	278.2	13 468	34 570	
-1	520c	24 520	26.51	-8.26	-59.73	60.3	0.8562	-1.2469	262.1	14 474	34 574	Bm
-1	530c	26 530	33.44	-21.88	-54.1	58.35	0.7192	-0.9929	247.9	15 478	35 577	
-1	540c	28 540	41.17	-34.9	-47.59	59.02	0.6418	-0.8082	233.7	16 481	36 581	
-1	544c	28 545	41.17	-34.9	-47.59	59.02	0.6418	-0.8082	233.7	16 481	36 581	
-1	550c	30 550	49.28	-45.91	-40.65	61.33	0.6082	-0.6758	221.5	16 483	37 585	
-1	554c	30 555	49.28	-45.91	-40.65	61.33	0.6082	-0.6758	221.5	16 483	37 585	
-1	560c	32 560	57.42	-53.67	-33.65	63.35	0.607	-0.5803	212.0	17 485	38 590	
W0	380	770	90.0	0.0	0.0	0.0	0.9809	-0.3459	0.0	$B_c=1,000$		
N0	380	770	3.6	0.0	0.0	0.0	0.9809	-0.3459	0.0	$x_c=0,000$		

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für P45, $Y_N=0$, $Y_W=90$, $Y_m=520_770$												
i_1, λ_1	i_2, λ_2	Y	A	B	C_{AB}	a	b	h_{xy}	i_d, λ_d	i_c, λ_c	Code	
1	405	33 566	52.74	-58.24	-27.46	64.39	0.5501	-0.5125	205.2	17 487	38 593	Cm
7	435	33 567	53.09	-66.54	-10.68	67.39	0.4904	-0.3847	189.1	18 491	-1 491c	
10	450	33 568	53.63	-73.81	5.63	74.02	0.4412	-0.2621	175.6	19 499	-1 499c	
12	460	33 569	54.32	-77.93	16.64	79.69	0.4179	-0.1816	167.9	21 507	-1 507c	
13	465	34 570	54.38	-79.27	21.3	82.08	0.4087	-0.1475	164.9	22 512	-1 512c	
13	470	34 571	55.8	-79.52	22.37	82.61	0.4217	-0.1438	164.2	22 514	-1 514c	Gm
15	475	34 574	57.32	-80.44	30.56	86.05	0.4304	-0.0909	159.1	25 528	-1 528c	
15	480	35 578	60.46	-80.03	32.94	86.54	0.4623	-0.0862	157.6	26 532	-1 532c	
17	485	37 587	64.69	-75.07	40.52	85.3	0.5276	-0.0536	151.6	28 544	-1 544c	
17	490	42 611	77.39	-52.64	50.16	72.71	0.7196	-0.0449	136.3	31 559	-1 559c	
19	495	-1 495c	85.02	-14.31	58.55	60.27	0.9244	-0.0287	103.7	33 569	12 463	max
20	500	-1 500c	83.68	-11.01	58.42	59.45	0.9391	-0.0249	100.6	34 570	13 466	
22	510	-1 510c	79.89	-1.85	56.73	56.76	0.9824	-0.0201	91.8	34 572	14 471	
24	520	-1 520c	74.47	10.28	53.24	54.22	1.047	-0.0182	79.0	34 574	15 475	Ym
26	530	-1 530c	67.75	23.68	48.46	53.94	1.1315	-0.0181	63.9	35 578	15 479	
27	540	-1 539c	64.04	30.31	45.74	54.87	1.1811	-0.0185	56.4	35 579	16 480	
29	545	-1 545c	56.19	42.54	39.87	58.31	1.2946	-0.0203	43.1	36 583	16 483	
29	550	-1 549c	56.19	42.54	39.87	58.31	1.2946	-0.0203	43.1	36 583	16 483	
30	555	-1 554c	52.13	47.79	36.82	60.33	1.3584	-0.0216	37.6	37 585	16 484	
31	560	-1 559c	48.05	52.25	33.73	62.2	1.4267	-0.0233	32.8	37 588	17 485	
33	566	1 405	47.25	58.24	27.46	64.39	1.4848	-0.0716	25.2	38 593	17 487	Rm
33	567	7 435	46.9	66.53	10.68	67.39	1.5591	-0.213	9.1	-1 491c	18 491	
33	568	10 450	46.36	73.8	-5.63	74.01	1.6284	-0.3528	355.6	-1 499c	19 499	
33	569	12 460	45.67	77.91	-16.64	79.67	1.6741	-0.4499	347.9	-1 507c	21 507	
34	570	13 465	45.61	79.25	-21.29	82.07	1.6868	-0.4909	344.9	-1 512c	22 512	
34	571	13 470	44.19	79.51	-22.37	82.59	1.7114	-0.5067	344.2	-1 514c	22 514	Mm
34	574	15 475	42.67	80.42	-30.55	86.03	1.7456	-0.5905	339.1	-1 528c	25 528	
35	578	15 480	39.53	80.01	-32.93	86.52	1.8013	-0.6374	337.6	-1 532c	26 532	
37	587	17 485	35.3	75.04	-40.5	85.28	1.8421	-0.7632	331.6	-1 544c	28 544	
42	611	17 490	22.6	52.62	-50.14	72.68	1.9229	-1.1914	316.3	-1 559c	31 559	
-1	495c	19 495	14.97	14.3	-58.52	60.24	1.3738	-1.8674	283.7	12 463	33 569	min
-1	500c	20 500	16.31	11.01	-58.39	59.42	1.2617	-1.7356	280.6	13 466	34 570	
-1	510c	22 510	20.1	1.85	-56.71	56.74	1.0286	-1.4324	271.8	14 471	34 572	
-1	520c	24 520	25.52	-10.28	-53.22	54.21	0.8305	-1.1384	259.0	15 475	34 574	Bm
-1	530c	26 530	32.24	-23.68	-48.45	53.93	0.6979	-0.9054	243.9	15 479	35 578	
-1	539c	27 540	35.95	-30.31	-45.73	54.87	0.6544	-0.813	236.4	16 480	35 579	
-1	545c	29 545	43.8	-42.54	-39.87	58.3	0.6033	-0.6682	223.1	16 483	36 583	
-1	549c	29 550	43.8	-42.54	-39.87	58.3	0.6033	-0.6682	223.1	16 483	36 583	
-1	554c	30 555	47.86	-47.79	-36.82	60.33	0.5923	-0.6119	217.6	16 484	37 585	
-1	559c	31 560	51.94	-52.25	-33.73	62.19	0.5894	-0.5639	212.8	17 485	37 588	
W0	380	770	90.0	0.0	0.0	0.0	0.9917	-0.3042	0.0	$B_c=1,000$		
N0	380	770	3.6	0.0	0.0	0.0	0.9917	-0.3042	0.0	$x_c=0,000$		

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für P40, $Y_N=0$, $Y_W=90$, $Y_m=520_770$												
i_1, λ_1	i_2, λ_2	Y	A	B	C_{AB}	a	b	h_{xy}	i_d, λ_d	i_c, λ_c	Code	
0	405	33 568	52.58	-61.26	-23.82	65.73	0.543	-0.4399	201.2	17 488	38 594	Cm
7	435	33 568	52.87	-68.13	-10.01	68.86	0.4936	-0.3344	188.3	18 493	-1 493c	
10	450	33 569	53.33	-74.23	3.59	74.32	0.4523	-0.2317	177.2	19 499	-1 499c	
12	460	34 570	53.28	-77.42	12.55	78.43	0.4278	-0.1644	170.7	21 507	-1 507c	
13	465	34 571	53.83	-78.58	16.9	80.38	0.4251	-0.133	167.8	22 512	-1 512c	
14	470	34 572	54.75	-79.33	20.89	82.04	0.4294	-0.106	165.2	23 519	-1 519c	Gm
14	475	34 574	56.7	-79.77	22.15	82.78	0.4463	-0.1023	164.4	24 522	-1 522c	
15	480	35 578	58.85	-79.36	26.33	83.62	0.4696	-0.0797	161.6	26 531	-1 531c	
17	485	37 585	62.11	-76.01	32.33	82.61	0.5194	-0.0504	156.9	28 543	-1 543c	
17	490	40 600	71.73	-63.89	38.54	74.62	0.6527	-0.0437	148.8	30 554	-1 554c	
19	495	-1 495c	85.57	-11.18	49.84	51.08	0.9567	-0.0256	102.6	34 571	12 464	max
20	500	-1 500c	84.33	-8.08	49.86	50.51	0.9706	-0.0221	99.2	34 571	13 467	
21	510	-1 509c	82.76	-4.16	49.48	49.66	0.9889	-0.0195	94.8	34 572	13 469	
24	520	-1 520c	75.67	12.33	45.96	47.59	1.0742	-0.0157	74.9	35 575	15 476	Ym
26	530	-1 530c	69.21	25.48	42.11	49.22	1.1562	-0.0153	58.8	35 578	16 480	
27	540	-1 539c	65.61	32.07	39.88	51.17	1.2045	-0.0155	51.1	36 580	16 481	
29	545	-1 545c	57.91	44.38	35.0	56.53	1.3156	-0.0168	38.2	36 584	16 484	
29	550	-1 549c	57.91	44.38	35.0	56.53	1.3156	-0.0168	38.2	36 584	16 484	
31	555	-1 555c	49.83	54.37	29.82	62.01	1.4455	-0.0192	28.7	37 588	17 486	
32	560	-1 560c	45.75	58.08	27.2	64.13	1.5168	-0.0208	25.0	38 591	17 487	
33	568	0 405	47.41	61.26	23.82	65.73	1.5259	-0.0576	21.2	38 594	17 488	Rm
33	568	7 435	47.12	68.13	10.01	68.86	1.5873	-0.1736	8.3	-1 493c	18 493	
33	569	10 450	46.66	74.22	-3.59	74.31	1.6453	-0.2894	357.2	-1 499c	19 499	
34	570	12 460	46.71	77.4	-12.54	78.41	1.6719	-0.3661	350.7	-1 507c	21 507	
34	571	13 465	46.16	78.57	-16.9	80.37	1.6899	-0.4051	347.8	-1 512c	22 512	
34	572	14 470	45.24	79.32	-20.89	82.02	1.7102	-0.4434	345.2	-1 519c	23 519	Mm
34	574	14 475	43.29	79.75	-22.15	82.77	1.7458	-0.4633	344.4	-1 522c	24 522	
35	578	15 480	41.14	79.34	-26.32	83.6	1.7805	-0.5146	341.6	-1 531c	26 531	
37	585	17 485	37.88	75.99	-32.32	82.58	1.8114	-0.5999	336.9	-1 543c	28 543	
40	600	17 490	28.26	63.87	-38.53	74.59	1.913	-0.804	328.8	-1 554c	30 554	
-1 495c	19 495	14.42	11.17	-49.82	51.06	1.3189	-1.6404	282.6	12 464	34 571	min	
-1 500c	20 500	15.66	8.08	-49.84	50.49	1.2155	-1.5316	279.2	13 467	34 571		
-1 509c	21 510	17.23	4.16	-49.46	49.64	1.1056	-1.4065	274.8	13 469	34 572		
-1 520c	24 520	24.32	-12.33	-45.95	47.58	0.8062	-1.0143	254.9	15 476	35 575	Bm	
-1 530c	26 530	30.78	-25.47	-42.1	49.21	0.6779	-0.8058	238.8	16 480	35 578		
-1 539c	27 540	34.38	-32.07	-39.87	51.17	0.6359	-0.7225	231.1	16 481	36 580		
-1 545c	29 545	42.08	-44.38	-35.0	56.52	0.5871	-0.5913	218.2	16 484	36 584		
-1 549c	29 550	42.08	-44.38	-35.0	56.52	0.5871	-0.5913	218.2	16 484	36 584		
-1 555c	31 555	50.16	-54.37	-29.82	62.01	0.5755	-0.4965	208.7	17 486	37 588		
-1 560c	32 560	54.24	-58.08	-27.2	64.13	0.5807	-0.4593	205.0	17 487	38 591		
W0	380	770	90.0	0.0	0.0	0.0	1.009	-0.2586	0.0	$B_c=1,000$		
N0	380	770	3.6	0.0	0.0	0.0	1.009	-0.2586	0.0	$x_c=0,000$		

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für P35, $Y_N=0$, $Y_W=90$, $Y_m=520_770$												
i_1, λ_1	i_2, λ_2	Y	A	B	C_{AB}	a	b	h_{xy}	i_d, λ_d	i_c, λ_c	Code	
1	405	34 570	51.69	-64.87	-19.6	67.77	0.5343	-0.3614	196.8	18 490	39 596	Cm
7	435	34 570	51.92	-69.87	-9.41	70.5	0.4981	-0.2822	187.6	18 494	47 638	
9	450	34 571	52.37	-73.08	-2.3	73.11	0.4782	-0.2272	181.8	19 498	-1 498c	
12	460	34 572	52.73	-77.25	8.87	77.75	0.4504	-0.1423	173.4	21 507	-1 507c	
12	465	34 572	53.37	-77.43	9.21	77.98	0.4561	-0.1406	173.2	21 508	-1 508c	
14	470	34 573	53.91	-78.91	15.68	80.46	0.4509	-0.0933	168.7	23 519	-1 519c	Gm
14	475	35 575	54.86	-79.1	16.17	80.74	0.4596	-0.0917	168.4	24 520	-1 520c	
15	480	35 578	57.07	-78.92	19.69	81.34	0.4832	-0.0716	165.9	26 530	-1 530c	
17	485	36 583	59.83	-76.21	24.51	80.06	0.5269	-0.0458	162.1	28 542	-1 542c	
18	490	38 593	66.26	-68.33	29.02	74.24	0.6239	-0.0344	156.9	30 552	-1 552c	
19	495	52 661	85.38	-11.45	39.95	41.56	0.9827	-0.0224	105.9	34 572	12 460	max
20	500	-1 500c	85.09	-5.08	40.54	40.85	1.0125	-0.0191	97.1	34 573	13 468	
22	510	-1 510c	81.87	3.06	39.86	39.98	1.0513	-0.0149	85.6	34 574	14 473	
23	520	-1 519c	79.68	8.35	39.03	39.91	1.0783	-0.0137	77.9	35 576	15 475	Ym
26	530	-1 530c	71.0	27.11	35.01	44.28	1.1891	-0.0124	52.2	35 579	16 481	
27	540	-1 539c	67.55	33.66	33.3	47.35	1.2357	-0.0125	44.6	36 581	16 483	
29	545	-1 545c	60.08	46.12	29.48	54.74	1.3435	-0.0133	32.5	37 585	17 486	
29	550	-1 549c	60.08	46.12	29.48	54.74	1.3435	-0.0133	32.5	37 585	17 486	
31	555	-1 555c	52.1	56.52	25.35	61.95	1.4703	-0.015	24.1	37 589	17 488	
32	560	-1 560c	48.02	60.5	23.23	64.81	1.5403	-0.0161	21.0	38 591	17 489	
34	570	1 405	48.3	64.87	19.6	67.77	1.5735	-0.0473	16.8	39 596	18 490	Rm
34	570	7 435	48.07	69.86	9.41	70.49	1.6176	-0.1313	7.6	47 638	18 494	
34	571	9 450	47.62	73.07	2.3	73.11	1.6501	-0.1903	1.8	-1 498c	19 498	
34	572	12 460	47.26	77.23	-8.87	77.74	1.69	-0.2847	353.4	-1 507c	21 507	
34	572	12 465	46.62	77.42	-9.21	77.97	1.7006	-0.2887	353.2	-1 508c	21 508	
34	573	14 470	46.08	78.9	-15.67	80.44	1.7213	-0.3457	348.7	-1 519c	23 519	Mm
35	575	14 475	45.13	79.09	-16.17	80.72	1.7373	-0.353	348.4	-1 520c	24 520	
35	578	15 480	42.92	78.9	-19.68	81.32	1.7716	-0.3931	345.9	-1 530c	26 530	
36	583	17 485	40.16	76.19	-24.5	80.04	1.7953	-0.4537	342.1	-1 542c	28 542	
38	593	18 490	33.73	68.31	-29.02	74.22	1.8463	-0.5537	336.9	-1 552c	30 552	
52	661	19 495	14.61	11.44	-39.94	41.55	1.3497	-1.3026	285.9	12 460	34 572	min
-1	500c	20 500	14.9	5.08	-40.52	40.84	1.1728	-1.2974	277.1	13 468	34 573	
-1	510c	22 510	18.12	-3.06	-39.85	39.97	0.9687	-1.0891	265.6	14 473	34 574	
-1	519c	23 520	20.31	-8.35	-39.02	39.9	0.8718	-0.9778	257.9	15 475	35 576	Bm
-1	530c	26 530	28.99	-27.11	-35.01	44.28	0.6623	-0.6927	232.2	16 481	35 579	
-1	539c	27 540	32.44	-33.66	-33.29	47.35	0.6213	-0.6202	224.6	16 483	36 581	
-1	545c	29 545	39.91	-46.12	-29.48	54.74	0.5742	-0.5051	212.5	17 486	37 585	
-1	549c	29 550	39.91	-46.12	-29.48	54.74	0.5742	-0.5051	212.5	17 486	37 585	
-1	555c	31 555	47.89	-56.52	-25.35	61.95	0.5643	-0.4214	204.1	17 488	37 589	
-1	560c	32 560	51.97	-60.5	-23.23	64.81	0.5707	-0.3884	201.0	17 489	38 591	
W0	380	770	89.99	0.0	0.0	0.0	1.0364	-0.2096	0.0	$B_c=1,000$		
N0	380	770	3.59	0.0	0.0	0.0	1.0364	-0.2096	0.0	$x_c=0,000$		

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für P30, $Y_N=0$, $Y_W=90$, $Y_m=520_770$												
i_1, λ_1	i_2, λ_2	Y	A	B	C_{AB}	a	b	h_{xy}	i_d, λ_d	i_c, λ_c	Code	
0	405	34 573	51.22	-68.72	-15.15	70.38	0.5434	-0.2765	192.4	18 493	39 598	Cm
6	435	34 573	51.43	-71.22	-10.2	71.95	0.5261	-0.2375	188.1	19 495	42 612	
10	450	34 573	51.68	-75.66	-0.31	75.66	0.4945	-0.1605	180.2	20 502	-1 502c	
12	460	34 574	52.01	-77.74	5.37	77.92	0.4823	-0.1168	176.0	21 508	-1 508c	
13	465	34 574	52.35	-78.54	8.08	78.96	0.48	-0.0963	174.1	22 512	-1 512c	
14	470	35 575	52.26	-78.76	10.29	79.43	0.4773	-0.0793	172.5	23 518	-1 518c	Gm
15	475	35 576	53.17	-78.75	12.54	79.74	0.4877	-0.0637	170.9	25 525	-1 525c	
16	480	35 579	54.74	-78.39	14.69	79.76	0.5073	-0.0507	169.3	26 533	-1 533c	
17	485	36 582	56.86	-76.94	16.75	78.74	0.5389	-0.0403	167.7	28 540	-1 540c	
18	490	37 589	61.42	-72.77	19.51	75.34	0.6062	-0.031	164.9	29 549	-1 549c	
19	495	41 606	71.0	-55.49	24.06	60.48	0.7675	-0.0225	156.5	32 561	-1 561c	
20	500	-1 500c	85.97	-2.17	30.6	30.68	1.07	-0.0157	94.0	35 575	13 469	max
21	510	-1 509c	84.73	1.13	30.62	30.64	1.0855	-0.0136	87.8	35 576	14 472	
24	520	-1 520c	78.86	15.82	29.17	33.18	1.1604	-0.0101	61.5	35 578	15 479	Ym
25	530	-1 529c	76.2	21.89	28.28	35.76	1.195	-0.0097	52.2	36 580	16 481	
28	540	-1 540c	66.53	41.21	24.72	48.06	1.3279	-0.0095	30.9	36 584	17 486	
29	545	-1 545c	62.86	47.43	23.31	52.85	1.3819	-0.0098	26.1	37 586	17 488	
30	550	-1 550c	59.03	53.23	21.82	57.53	1.4408	-0.0102	22.2	37 588	17 489	
31	555	-1 555c	55.07	58.42	20.28	61.84	1.5045	-0.0108	19.1	38 590	18 490	
32	560	-1 560c	51.03	62.81	18.69	65.54	1.5725	-0.0116	16.5	38 592	18 491	
34	573	0 405	48.77	68.72	15.15	70.37	1.6437	-0.0338	12.4	39 598	18 493	Rm
34	573	6 435	48.56	71.22	10.2	71.95	1.6667	-0.0741	8.1	42 612	19 495	
34	573	10 450	48.31	75.65	0.31	75.65	1.7064	-0.1555	0.2	-1 502c	20 502	
34	574	12 460	47.98	77.73	-5.37	77.91	1.7281	-0.2029	356.0	-1 508c	21 508	
34	574	13 465	47.64	78.53	-8.08	78.95	1.7395	-0.226	354.1	-1 512c	22 512	
35	575	14 470	47.73	78.75	-10.29	79.42	1.74	-0.2444	352.5	-1 518c	23 518	Mm
35	576	15 475	46.82	78.73	-12.54	79.73	1.7527	-0.2653	350.9	-1 525c	25 525	
35	579	16 480	45.25	78.37	-14.69	79.74	1.7729	-0.288	349.3	-1 533c	26 533	
36	582	17 485	43.13	76.92	-16.74	78.72	1.7935	-0.3134	347.7	-1 540c	28 540	
37	589	18 490	38.57	72.75	-19.51	75.32	1.8346	-0.3605	344.9	-1 549c	29 549	
41	606	19 495	28.99	55.47	-24.06	60.47	1.8456	-0.4901	336.5	-1 561c	32 561	
-1	500c	20 500	14.02	2.17	-30.6	30.67	1.1422	-1.0308	274.0	13 469	35 575	min
-1	509c	21 510	15.26	-1.13	-30.61	30.63	1.0503	-0.9601	267.8	14 472	35 576	
-1	520c	24 520	21.13	-15.82	-29.16	33.18	0.7807	-0.7102	241.5	15 479	35 578	Bm
-1	529c	25 530	23.79	-21.89	-28.27	35.76	0.7121	-0.6335	232.2	16 481	36 580	
-1	540c	28 540	33.46	-41.21	-24.72	48.06	0.5875	-0.4536	210.9	17 486	36 584	
-1	545c	29 545	37.13	-47.43	-23.31	52.85	0.5692	-0.4092	206.1	17 488	37 586	
-1	550c	30 550	40.96	-53.23	-21.82	57.53	0.5603	-0.3712	202.2	17 489	37 588	
-1	555c	31 555	44.92	-58.42	-20.28	61.84	0.5599	-0.3387	199.1	18 490	38 590	
-1	560c	32 560	48.96	-62.81	-18.69	65.54	0.5669	-0.3109	196.5	18 491	38 592	
W0	380	770	90.0	0.0	0.0	0.0	1.0801	-0.1581	0.0	$B_c=1,000$		
N0	380	770	3.6	0.0	0.0	0.0	1.0801	-0.1581	0.0	$x_c=0,000$		

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für P25, $Y_N=0$, $Y_W=90$, $Y_m=520_770$												
i_1, λ_1	i_2, λ_2	Y	A	B	C_{AB}	a	b	h_{xy}	i_d, λ_d	i_c, λ_c	Code	
1	405	35 576	49.8	-72.99	-10.51	73.74	0.5653	-0.1908	188.1	19 497 40 601	Cm	
6	435	35 576	49.94	-74.35	-7.78	74.76	0.556	-0.1686	185.9	19 499 42 611		
10	450	35 577	50.11	-77.06	-1.61	77.08	0.5364	-0.1192	181.1	20 504 -1 504c		
11	460	35 577	50.41	-77.81	0.31	77.81	0.5342	-0.1038	179.7	21 506 -1 506c		
13	465	35 577	50.55	-78.85	3.99	78.95	0.5276	-0.0747	177.0	22 513 -1 513c		
14	470	35 578	50.92	-79.15	5.68	79.35	0.5297	-0.0617	175.8	23 518 -1 518c	Gm	
15	475	35 579	51.52	-79.24	7.2	79.57	0.5363	-0.0504	174.8	25 525 -1 525c		
16	480	36 580	51.92	-78.93	8.43	79.38	0.5435	-0.0413	173.8	26 531 -1 531c		
17	485	36 582	53.69	-77.94	9.82	78.56	0.5708	-0.0331	172.8	27 539 -1 539c		
18	490	37 586	56.27	-75.95	11.24	76.78	0.6116	-0.0264	171.5	29 546 -1 546c		
18	495	38 594	62.51	-71.25	12.89	72.4	0.6956	-0.0238	169.7	30 553 -1 553c		
20	500	44 620	75.83	-38.16	17.53	41.99	0.9502	-0.0138	155.3	34 570 -1 570c		
21	510	-1 509c	85.96	3.19	20.63	20.87	1.1664	-0.0103	81.2	35 578 14 474	max	
24	520	-1 520c	81.0	16.47	20.04	25.94	1.2329	-0.0073	50.5	36 581 16 481	Ym	
25	530	-1 529c	78.68	22.19	19.56	29.58	1.2643	-0.0068	41.4	36 582 16 484		
28	540	-1 540c	69.94	41.18	17.48	44.74	1.387	-0.0063	22.9	37 586 17 489		
28	545	-1 544c	69.94	41.18	17.48	44.74	1.387	-0.0063	22.9	37 586 17 489		
29	550	-1 549c	66.52	47.59	16.61	50.4	1.4377	-0.0064	19.2	37 588 18 491		
30	555	-1 554c	62.89	53.73	15.67	55.96	1.4932	-0.0066	16.2	37 589 18 492		
32	560	-1 560c	55.14	64.38	13.64	65.81	1.6186	-0.0073	11.9	38 594 18 494		
35	576	1 405	50.19	72.98	10.51	73.74	1.7332	-0.0225	8.1	40 601 19 497	Rm	
35	576	6 435	50.05	74.35	7.78	74.75	1.7457	-0.0441	5.9	42 611 19 499		
35	577	10 450	49.88	77.05	1.61	77.07	1.7694	-0.0934	1.1	-1 504c 20 504		
35	577	11 460	49.58	77.8	-0.31	77.8	1.7792	-0.1088	359.7	-1 506c 21 506		
35	577	13 465	49.44	78.84	-3.99	78.94	1.7894	-0.1387	357.0	-1 513c 22 513		
35	578	14 470	49.08	79.13	-5.68	79.34	1.7965	-0.1526	355.8	-1 518c 23 518	Mm	
35	579	15 475	48.47	79.23	-7.2	79.56	1.8054	-0.1658	354.8	-1 525c 25 525		
36	580	16 480	48.07	78.92	-8.43	79.37	1.8082	-0.1765	353.8	-1 531c 26 531		
36	582	17 485	46.3	77.93	-9.81	78.55	1.8248	-0.1911	352.8	-1 539c 27 539		
37	586	18 490	43.72	75.94	-11.24	76.77	1.8463	-0.2092	351.5	-1 546c 29 546		
38	594	18 495	37.48	71.23	-12.89	72.39	1.9117	-0.2439	349.7	-1 553c 30 553		
44	620	20 500	24.16	38.15	-17.52	41.98	1.783	-0.3964	335.3	-1 570c 34 570		
-1	509c	21 510	14.03	-3.18	-20.62	20.87	1.0606	-0.694	261.2	14 474 35 578	min	
-1	520c	24 520	18.99	-16.47	-20.04	25.94	0.8046	-0.5283	230.5	16 481 36 581	Bm	
-1	529c	25 530	21.31	-22.18	-19.56	29.58	0.7352	-0.4734	221.4	16 484 36 582		
-1	540c	28 540	30.05	-41.18	-17.48	44.74	0.6034	-0.339	202.9	17 489 37 586		
-1	544c	28 545	30.05	-41.18	-17.48	44.74	0.6034	-0.339	202.9	17 489 37 586		
-1	549c	29 550	33.47	-47.59	-16.61	50.4	0.5828	-0.3048	199.2	18 491 37 588		
-1	554c	30 555	37.1	-53.73	-15.67	55.97	0.5723	-0.2753	196.2	18 492 37 589		
-1	560c	32 560	44.85	-64.39	-13.64	65.82	0.5773	-0.228	191.9	18 494 38 594		
W0	380	770	90.0	0.0	0.0	0.0	1.1515	-0.1063	0.0	$B_c=1,000$		
N0	380	770	3.6	0.0	0.0	0.0	1.1515	-0.1063	0.0	$x_c=0,000$		