

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für A00, Y_N=3,6, Y_W=90, Y_m=520 770

l ₁	l ₂	l ₃	Y	A ₁	B ₁	C _{AB1}	a ₁	b ₁	h _{xy1}	l _d	l _e	l _c	λ _c	Code	
1	405	34	574	45.93	-59.57	-12.24	60.82	0.3094	-0.2489	191.6	18	494	39	599	Cm
6	435	34	574	46.09	-60.23	-8.5	60.83	0.3056	-0.2161	188.0	19	496	42	612	
9	450	34	574	46.35	-60.40	-2.79	61.11	0.3015	-0.1664	182.6	20	501	-1	501e	
12	460	35	575	46.0	-61.33	3.74	61.44	0.295	-0.1097	176.5	21	508	-1	508e	
13	465	35	575	46.26	-61.2	5.94	61.49	0.2991	-0.0909	174.2	22	512	-1	512e	
13	470	35	576	46.86	-61.21	6.51	61.51	0.3058	-0.0897	174.2	22	513	-1	513e	
14	475	35	577	47.65	-60.91	8.27	61.47	0.3169	-0.0727	172.2	23	519	-1	519e	Gm
16	480	35	579	48.7	-59.74	11.48	60.83	0.3376	-0.0479	169.1	26	533	-1	533e	
17	485	36	582	50.33	-58.25	13.07	59.7	0.3653	-0.0383	167.3	28	540	-1	540e	
18	490	37	588	53.85	-54.96	15.14	57.01	0.42	-0.0228	165.5	29	548	-1	548e	
19	495	40	601	61.06	-44.1	18.35	47.76	0.5394	-0.0292	154.7	31	559	-1	559e	
20	500	-1	500e	77.63	5.72	24.77	25.42	0.8578	-0.0146	76.9	35	576	13	469	max
21	510	-1	509e	76.57	8.29	24.82	26.17	0.8716	-0.0126	71.5	35	576	14	472	
24	520	-1	520e	71.52	19.47	23.77	30.73	0.9372	-0.0093	50.6	35	579	16	480	Ym
26	530	-1	530e	66.62	28.9	22.27	36.49	1.0018	-0.0085	37.6	36	582	16	484	
28	540	-1	540e	60.72	38.73	20.3	43.73	1.0834	-0.0085	27.6	37	585	17	487	
28	545	-1	544e	60.72	38.73	20.3	43.73	1.0834	-0.0085	27.6	37	585	17	487	
29	550	-1	549e	57.48	43.44	19.18	47.49	1.1306	-0.0087	23.8	37	586	17	489	
31	555	-1	555e	50.54	51.76	16.76	54.41	1.2379	-0.0096	17.9	38	590	18	491	
32	560	-1	560e	46.93	55.05	15.48	57.19	1.2975	-0.0102	15.7	38	593	18	492	
34	574	1	405	44.06	59.57	12.24	60.81	1.369	-0.0311	11.6	39	599	18	494	Rm
34	574	6	435	43.9	60.23	8.5	60.83	1.3771	-0.0647	8.0	42	612	19	496	
34	574	9	450	43.64	61.04	2.79	61.1	1.3877	-0.1166	2.6	-1	501e	20	501	
35	575	12	460	43.99	61.32	-3.74	61.44	1.3858	-0.1763	356.5	-1	508e	21	508	
35	575	13	465	43.73	61.19	-5.94	61.48	1.388	-0.1966	354.4	-1	512e	22	512	
35	576	13	470	43.13	61.2	-6.15	61.5	1.3958	-0.1993	354.2	-1	513e	22	513	
35	577	14	475	42.34	60.9	-8.27	61.46	1.4036	-0.2204	352.2	-1	519e	23	519	Mm
35	579	16	480	41.29	59.73	-11.48	60.82	1.4069	-0.2535	349.1	-1	533e	26	533	
36	582	17	485	39.66	58.24	-13.07	59.69	1.4155	-0.2741	347.3	-1	540e	28	540	
37	588	18	490	36.14	54.95	-15.13	57.0	1.4364	-0.3098	344.5	-1	548e	29	548	
40	601	19	495	28.93	44.09	-18.34	47.75	1.4379	-0.3959	337.4	-1	559e	31	559	
-1	500e	20	500	12.36	-5.72	-24.76	25.41	0.6431	-0.9436	256.9	13	469	35	576	min
-1	509e	21	510	13.42	-8.29	-24.81	26.16	0.581	-0.8819	251.5	14	472	35	576	
-1	520e	24	520	18.47	-19.47	-23.77	30.72	0.4067	-0.6569	230.6	16	480	35	579	Bm
-1	530e	26	530	23.37	-28.9	-22.27	36.49	0.3337	-0.5233	217.6	16	484	36	582	
-1	540e	28	540	29.27	-38.72	-20.3	43.72	0.299	-0.4197	207.6	17	487	37	585	
-1	544e	28	545	29.27	-38.72	-20.3	43.72	0.299	-0.4197	207.6	17	487	37	585	
-1	549e	29	550	32.51	-43.44	-19.18	47.49	0.2938	-0.3783	203.8	17	489	37	586	
-1	555e	31	555	39.45	-51.76	-16.76	54.41	0.3034	-0.3122	197.9	18	491	38	590	
-1	560e	32	560	43.06	-55.06	-15.48	57.19	0.3169	-0.2861	195.7	18	492	38	593	
W0	380	770	89.99	0.0	0.0	0.0	0.8283	-0.1422	0.0	B _c =1,000					
N0	380	770	3.59	0.0	0.0	0.0	0.8283	-0.1422	0.0	x _c =0,110					

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für A00, Y_N=3,6, Y_W=90, Y_m=520 770

l ₁	l ₂	l ₃	Y	A ₂	B ₂	C _{AB2}	a ₂	b ₂	h _{xy2}	l _d	l _e	l _c	λ _c	Code	
1	405	34	574	45.93	-59.57	-30.6	66.98	0.3094	-0.2489	207.1	18	494	39	599	Cm
6	435	34	574	46.09	-60.23	-21.26	63.88	0.3056	-0.2161	199.4	19	496	42	612	
9	450	34	574	46.35	-61.04	-6.98	61.44	0.3015	-0.1664	186.5	20	501	-1	501e	
12	460	35	575	46.0	-61.33	9.36	62.04	0.295	-0.1097	171.3	21	508	-1	508e	
13	465	35	575	46.26	-61.2	14.85	62.98	0.2991	-0.0909	166.3	22	512	-1	512e	
13	470	35	576	46.86	-61.21	15.38	63.11	0.3058	-0.0897	163.8	22	513	-1	513e	
14	475	35	577	47.65	-60.91	20.69	64.33	0.3169	-0.0727	161.2	23	519	-1	519e	Gm
16	480	35	579	48.7	-59.74	27.81	66.28	0.3376	-0.0479	154.3	26	533	-1	533e	
17	485	36	582	50.33	-58.25	32.69	66.8	0.3653	-0.0383	150.6	28	540	-1	540e	
18	490	37	588	53.85	-54.96	37.85	66.73	0.42	-0.0298	145.4	29	548	-1	548e	
19	495	40	601	61.06	-44.1	45.87	63.63	0.5394	-0.0232	133.8	31	559	-1	559e	
20	500	-1	500e	77.63	5.72	61.93	62.19	0.8578	-0.0146	84.7	35	576	13	469	max
21	510	-1	509e	76.57	8.29	62.05	62.61	0.8716	-0.0126	82.3	35	576	14	472	
24	520	-1	520e	71.52	19.47	59.43	62.54	0.9372	-0.0093	71.8	35	579	16	480	Ym
26	530	-1	530e	66.62	28.9	55.68	62.74	1.0018	-0.0085	62.5	36	582	16	484	
28	540	-1	540e	60.72	38.73	50.76	63.85	1.0834	-0.0085	52.6	37	585	17	487	
28	545	-1	544e	60.72	38.73	50.76	63.85	1.0834	-0.0085	52.6	37	585	17	487	
29	550	-1	549e	57.48	43.44	47.97	64.72	1.1306	-0.0087	47.8	37	586	17	489	
31	555	-1	555e	50.54	51.76	41.9	66.6	1.2379	-0.0096	38.9	38	590	18	491	
32	560	-1	560e	46.93	55.05	38.72	67.31	1.2975	-0.0102	35.1	38	593	18	492	
34	574	1	405	44.06	59.57	30.6	66.97	1.369	-0.0311	27.1	39	599	18	494	Rm
34	574	6	435	43.9	60.23	21.26	63.87	1.3771	-0.0647	21.6	42	612	19	496	
34	574	9	450	43.64	61.04	6.98	61.43	1.3877	-0.1166	6.5	-1	501e	20	501	
35	575	12	460	43.99	61.32	-9.36	62.03	1.3858	-0.1763	351.3	-1	508e	21	508	
35	575	13	465	43.73	61.19	-14.85	62.97	1.388	-0.1966	346.3	-1	512e	22	512	
35	576	13	470	43.13	61.2	-15.38	63.1	1.3958	-0.1993	345.8	-1	513e	22	513	
35	577	14	475	42.34	60.9	-18.69	64.32	1.4036	-0.2204	341.2	-1	519e	23	519	Mm
35	579	16	480	41.29	59.73	-28.71	66.27	1.4069	-0.2535	334.3	-1	533e	26	533	
36	582	17	485	39.66	58.24	-32.69	66.78	1.4155	-0.2741	330.6	-1	540e	28	540	
37	588	18	490	36.14	54.95	-37.84	66.72	1.4364	-0.3098	325.4	-1	548e	29	548	
40	601	19	495	28.93	44.09	-45.86	63.62	1.4379	-0.3959	313.8	-1	559e	31	559	
-1	500e	20	500	12.36	-5.72	-61.91	62.17	0.6431	-0.9436	264.2	13	469	35	576	min
-1	509e	21	510	13.42	-8.29	-62.04	62.59	0.581	-0.8819	262.3	14	472	35	576	
-1	520e	24	520	18.47	-19.47	-59.43	62.53	0.4067	-0.6569	251.8	16	480	35	579	Bm
-1	530e	26	530	23.37	-28.9	-55.68	62.73	0.3337	-0.5233	242.5	16	484	36	582	
-1	540e	28	540	29.27	-38.72	-50.76	63.85	0.299	-0.4197	232.6	17	487	37	585	
-1	544e	28	545	29.27	-38.72	-50.76	63.85	0.299	-0.4197	232.6	17	487	37	585	
-1	549e	29	550	32.51	-43.44	-47.97	64.72	0.2938	-0.3783	227.8	17	489	37	586	
-1	555e	31	555	39.45	-51.76	-41.9	66.6	0.3034	-0.3122	218.9	18	491	38	590	
-1	560e	32	560	43.06	-55.06	-38.72	67.31	0.3169	-0.2861	215.1	18	492	38	593	
W0	380	770	89.99	0.0	0.0	0.0	0.8283	-0.3557	0.0	B _c =2,500					
N0	380	770	3.59	0.0	0.0	0.0	0.8283	-0.3557	0.0	x _c =0,11					