









Oswald optimal colours (o), maximum (m) C_{AB} for D65, $Y_N=3.6$, $Y_W=90$, $Y_M=520/770$

λ_1	λ_2	X	Y	Z	x	y	z	h_{xy}	l_d	l_d	l_c	l_c	λ_c	Code
0	405	32	561	28.34	48.4	87.6	0.1724	0.2945	0.533	193.8	16	483	37	589 Cm
6	435	32	562	25.69	48.95	72.52	0.1746	0.3326	0.4927	178.5	17	486	42	610
10	450	32	563	21.01	49.59	44.51	0.1829	0.4317	0.3752	141.6	19	496	-1	496c
12	460	33	565	19.15	49.94	29.98	0.1933	0.504	0.3026	124.2	21	505	-1	505c
12	465	33	567	20.12	51.15	29.99	0.1987	0.5051	0.2961	122.8	21	506	-1	506c
14	470	33	569	19.94	52.23	19.06	0.2186	0.5724	0.2089	111.1	24	520	-1	520c
15	475	34	573	21.65	54.1	15.12	0.2382	0.5953	0.1664	105.6	25	528	-1	528cM
16	480	36	580	25.4	57.45	12.12	0.2674	0.6048	0.1276	99.2	27	537	-1	537c
17	485	39	595	35.62	64.35	9.93	0.3241	0.5855	0.0903	87.4	29	548	-1	548c
18	490	-1	490c	63.02	76.18	8.3	0.4272	0.5164	0.0562	58.5	33	565	11	459 max
19	495	-1	495c	62.98	75.01	7.04	0.4342	0.5171	0.0485	57.1	33	566	12	462
20	500	-1	500c	62.97	73.55	6.07	0.4416	0.5158	0.0425	55.3	33	567	12	464
22	510	-1	510c	62.87	69.55	4.8	0.4581	0.5068	0.0305	50.6	33	569	13	469
23	520	-1	519c	62.69	66.99	4.43	0.4674	0.4995	0.033	47.7	34	570	14	471 Ym
25	530	-1	529c	61.81	60.81	3.97	0.4882	0.4803	0.0314	40.7	34	573	15	475
27	540	-1	539c	60.05	53.7	3.73	0.511	0.4571	0.0318	32.8	35	577	15	478
28	545	-1	544c	58.8	49.99	3.67	0.5228	0.4445	0.0326	28.7	35	579	15	479
29	550	-1	549c	57.28	46.21	3.62	0.5347	0.4313	0.0338	24.7	36	582	16	480
30	555	-1	554c	55.49	42.43	3.6	0.5465	0.4179	0.0354	20.8	36	584	16	481
32	560	-1	560c	51.12	35.12	3.57	0.5691	0.391	0.0397	13.6	37	589	16	483
32	561	0	405	57.19	41.59	10.39	0.5238	0.3809	0.0951	13.8	37	589	16	483 Rm
32	562	6	435	59.84	41.04	25.47	0.4735	0.3248	0.2016	35.8	42	610	17	486
32	563	10	450	64.52	40.4	53.74	0.4066	0.2546	0.3387	321.6	-1	496	19	496
33	565	12	460	66.38	40.05	68.01	0.3805	0.2295	0.3989	304.3	-1	505	21	505
33	567	12	465	65.41	38.84	68.01	0.3797	0.2254	0.3947	302.9	-1	506	21	506
33	569	14	470	65.59	37.76	78.93	0.3598	0.2071	0.433	291.1	-1	520	24	520
34	573	15	475	63.88	35.89	82.87	0.3497	0.1964	0.4537	285.6	-1	528	25	528 Mm
36	580	16	480	60.13	32.54	85.86	0.3367	0.1822	0.4809	279.3	-1	537	27	537
39	595	17	485	49.91	25.64	88.07	0.305	0.1567	0.5382	267.4	-1	548	29	548
-1	490c	18	490	22.51	13.81	89.7	0.1786	0.1096	0.7117	238.5	11	459	33	565 min
-1	495c	19	495	22.55	14.98	90.95	0.1755	0.1166	0.7078	237.1	12	462	33	566
-1	500c	20	500	22.56	16.44	91.92	0.1723	0.1256	0.702	235.4	12	464	33	567
-1	510c	22	510	22.66	20.44	93.19	0.1662	0.1499	0.6837	230.7	13	469	33	569
-1	519c	23	520	22.84	23.0	93.56	0.1638	0.165	0.6711	227.7	14	471	34	570 Bm
-1	529c	25	530	23.72	29.18	94.02	0.1614	0.1986	0.6399	220.7	15	475	34	573
-1	539c	27	540	25.48	36.29	94.26	0.1633	0.2325	0.604	212.8	15	478	35	577
-1	544c	28	545	26.73	40.91	94.33	0.1659	0.2483	0.5856	208.8	15	479	35	579
-1	549c	29	550	28.25	43.78	94.37	0.1697	0.2631	0.567	204.7	16	480	36	582
-1	554c	30	555	30.04	47.56	94.4	0.1746	0.2765	0.5488	200.8	16	481	36	584
-1	560c	32	560	34.41	54.87	94.43	0.1873	0.2986	0.5139	193.6	16	483	37	589
W0	380	770	85.53	90.0	98.0	0.3127	0.329	0.3582	0.0					
N0	380	770	3.42	3.6	3.92	0.3127	0.329	0.3582	0.0					



TUB-test chart DEF0; Oswald optimal colours, $Y_N=3.6$, $Y_W=90$, illuminant D65, CIE-02-degree
 Oswald optimal colour data: XYZ and eight different colour diagrams,

TUB registration: 2022.11.01-DEF0/DEFOL01.TXT /PS
 application for evaluation and measurement of display or print output
 TUB material: code=thadta