

Farbmetrische Daten von Fernseh-Lichtfarben-System TLS11 für Helligkeit $L^*_N=11$ von Schwarz

System:
TLS11
Monitor:
LCD

Farbe	$r=ol^*1$	$g=ol^*2$	$b=ol^*3$	$L^*_2=LAB^*1c$	$a^*_c=LAB^*2c$	$b^*_c=LAB^*3c$	$C^*_{ab}=LAB^*rc$	h_{abc}	$X_c=XYZ^*1c$	$Y_c=XYZ^*2c$	$Z_c=XYZ^*3c$	x_c	y_c	$Y_{88.59}$
00 00y	1.0	0.0	0.0	78.64	58.52	98.03	37	42.14	22.17	3.33	0.623	0.3278	0.2503	
01 013y	1.0	0.125	0.0	54.91	76.45	59.02	96.58	38	42.42	22.84	3.44	0.6174	0.3325	0.2579
02 025y	1.0	0.25	0.0	57.87	68.1	61.12	91.5	42	43.91	25.83	3.96	0.5958	0.3505	0.2916
03 038y	1.0	0.375	0.0	62.22	56.16	64.44	85.47	49	46.26	30.66	4.75	0.5664	0.3754	0.3461
04 050y	1.0	0.5	0.0	67.48	42.42	68.19	80.31	58	49.48	37.97	5.91	0.5384	0.4022	0.4207
05 063y	1.0	0.625	0.0	73.63	27.43	72.96	77.94	70	53.85	46.12	7.39	0.5016	0.4296	0.5206
06 075y	1.0	0.75	0.0	80.08	12.73	77.89	78.93	81	59.14	56.82	9.2	0.4725	0.454	0.6414
07 088y	1.0	0.875	0.0	86.52	-1.05	82.98	82.99	91	65.14	69.03	11.22	0.448	0.4748	0.7793
08 y001	1.0	1.0	0.0	94.11	-15.83	89.38	90.77	101	73.43	85.54	13.8	0.425	0.4951	0.9655
09 y131	0.875	1.0	0.0	92.0	-27.1	86.39	90.55	108	64.07	80.71	13.54	0.4047	0.5098	0.911
10 y251	0.75	1.0	0.0	90.22	-37.49	83.97	91.96	115	56.47	76.78	13.28	0.3854	0.524	0.8667
11 y381	0.625	1.0	0.0	88.56	-48.25	81.77	94.94	122	49.95	73.23	13.01	0.3649	0.5393	0.8267
12 y501	0.5	1.0	0.0	87.07	-58.61	79.85	99.05	138	36.56	70.43	12.75	0.3469	0.5545	0.7917
13 y631	0.375	1.0	0.0	85.89	-67.53	78.43	103.5	132	39.02	67.76	12.81	0.3271	0.568	0.7649
14 y751	0.25	1.0	0.0	84.97	-74.95	77.13	107.56	136	35.55	65.95	12.4	0.3121	0.579	0.7444
15 y881	0.125	1.0	0.0	84.37	-79.89	76.36	110.52	138	33.36	64.77	12.3	0.3021	0.5865	0.7312
16 000c	0.0	1.0	0.0	84.21	-81.1	76.13	111.24	138	32.83	64.47	12.29	0.2996	0.5883	0.7278
17 113c	0.0	1.0	0.125	84.25	-80.71	73.57	109.22	139	32.98	64.54	13.31	0.2976	0.5823	0.7285
18 125c	0.0	1.0	0.25	84.35	-78.62	63.95	105.25	143	33.71	64.74	17.66	0.2903	0.5576	0.7308
19 138c	0.0	1.0	0.375	84.61	-75.49	51.46	91.37	148	34.93	65.24	24.72	0.2797	0.5224	0.7365
20 150c	0.0	1.0	0.5	84.97	-71.46	38.14	81.04	154	36.59	65.95	34.2	0.2676	0.4823	0.7444
21 163c	0.0	1.0	0.625	85.43	-66.43	24.55	70.83	163	38.75	66.85	46.23	0.2592	0.4403	0.7566
22 175c	0.0	1.0	0.75	85.97	-61.24	11.9	62.39	173	41.15	67.93	59.93	0.2435	0.4019	0.7668
23 188c	0.0	1.0	0.875	86.54	-56.04	0.7	56.06	183	43.7	69.07	74.31	0.2336	0.3692	0.7796
24 c00v	0.0	1.0	1.0	87.18	-51.1	-9.41	51.97	195	46.37	70.38	89.45	0.2249	0.3413	0.7944
25 c13v	0.0	0.875	1.0	78.68	-38.63	-22.32	44.62	213	38.35	54.38	86.97	0.2134	0.3026	0.6138
26 c25v	0.0	0.75	1.0	71.08	-26.3	-33.97	42.97	233	32.33	42.3	84.93	0.2026	0.2651	0.4775
27 c38v	0.0	0.675	1.0	63.12	-11.97	-46.39	47.92	254	27.09	31.73	83.16	0.1908	0.2235	0.3855
28 c50v	0.0	0.5	1.0	54.95	4.19	-59.11	59.26	272	22.65	22.88	80.45	0.1786	0.1804	0.2582
29 c63v	0.0	0.375	1.0	41.37	21.46	-71.55	74.71	284	19.44	16.3	79.49	0.1673	0.1403	0.184
30 c75v	0.0	0.25	1.0	40.42	39.44	-83.05	91.73	294	16.99	11.37	79.29	0.1578	0.1056	0.1284
31 c88v	0.0	0.125	1.0	34.57	55.15	-92.53	107.73	299	15.49	8.29	79.02	0.1507	0.0806	0.0935
32 v00m	0.0	0.0	1.0	33.09	59.26	-94.9	113.39	301	15.11	7.58	78.79	0.1489	0.0747	0.0856
33 v131m	0.125	0.0	1.0	33.6	60.17	-94.39	111.95	301	15.63	7.82	79.26	0.1522	0.0761	0.0882
34 v251m	0.25	0.0	1.0	35.64	62.25	-90.58	109.92	303	17.57	8.82	78.88	0.1669	0.0838	0.0996
35 v381m	0.375	0.0	1.0	38.78	65.67	-85.41	107.74	306	20.9	10.53	79.21	0.1889	0.0952	0.1139
36 v501m	0.5	0.0	1.0	42.38	69.54	-79.14	105.36	310	25.19	12.75	79.11	0.2152	0.1089	0.1489
37 v631m	0.625	0.0	1.0	46.58	74.48	-72.19	103.73	315	31.01	15.7	79.49	0.2457	0.1244	0.1772
38 v751m	0.75	0.0	1.0	50.83	79.05	-64.9	102.28	320	37.61	19.12	79.55	0.276	0.1403	0.2158
39 v881m	0.875	0.0	1.0	54.98	83.66	-57.89	101.73	324	44.97	22.91	79.74	0.3046	0.1552	0.2586
40 m00o	1.0	0.0	1.0	59.56	89.09	-50.27	102.3	329	54.26	27.64	80.12	0.3349	0.1706	0.312
41 m13o	1.0	0.0	0.875	58.35	87.39	-40.57	96.35	334	51.59	26.33	65.42	0.3599	0.1837	0.2972
42 m25o	1.0	0.0	0.75	57.23	85.38	-29.34	90.29	340	49.04	25.16	51.28	0.3908	0.2005	0.284
43 m38o	1.0	0.0	0.675	56.14	83.38	-16.14	84.93	348	46.62	24.05	37.77	0.4299	0.2218	0.2715
44 m50o	1.0	0.0	0.5	55.19	81.22	-0.89	81.23	359	44.43	23.11	25.72	0.4764	0.2478	0.2609
45 m63o	1.0	0.0	0.375	53.75	79.62	15.48	79.62	371	42.67	22.81	16.14	0.526	0.275	0.2518
46 m75o	1.0	0.0	0.25	53.75	78.41	33.44	85.24	24	41.41	21.74	8.91	0.5747	0.3017	0.2454
47 m88o	1.0	0.0	0.125	53.35	77.5	51.81	93.22	34	40.55	21.37	4.23	0.613	0.323	0.2412
48 o00y	1.0	0.0	0.0	54.21	78.64	58.52	98.03	37	42.14	22.17	3.33	0.623	0.3278	0.2503
49 n00w	0.0	0.0	0.0	10.76	5.51	-3.96	6.79	0	1.34	1.23	1.71	0.3134	0.2867	0.0139
50 n13w	0.125	0.125	0.125	16.56	4.87	-3.31	5.9	169	2.33	2.21	2.86	0.3146	0.2988	0.025
51 n25w	0.25	0.25	0.25	30.75	4.15	-2.76	4.99	269	6.61	6.54	7.89	0.3142	0.311	0.0739
52 n38w	0.375	0.375	0.375	43.53	4.11	-2.65	4.9	292	13.48	13.52	15.89	0.3142	0.3152	0.1526
53 n50w	0.5	0.5	0.5	45.06	4.05	-2.42	4.73	297	23.73	26.55	29.27	0.315	0.3181	0.2595
54 n63w	0.625	0.625	0.625	66.15	3.69	-1.8	4.11	298	34.83	35.52	40.18	0.3151	0.3214	0.401
55 n75w	0.75	0.75	0.75	76.28	3.24	-0.77	3.34	301	49.73	50.35	55.64	0.3163	0.3248	0.5683
56 n88w	0.875	0.875	0.875	85.51	2.1	0.82	2.26	299	64.62	67.02	71.95	0.3174	0.3292	0.7565
57 n99w	1.0	1.0	1.0	95.41	-0.21	4.78	4.79	0	84.08	88.59	89.43	0.3208	0.338	1.0

KG37-79, 1-66

Stiehe Original/Kopie: http://web.me.com/Klaus_richter/KG37/KG37L0N1.TXT / PS
 Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>

TUB-Registrierung: 20100601_KG37/KG37L0N1.TXT / PS
 Anwendung für Messung von Drucker- oder Monitorssystemen

TUB-Material: Code=th4ta