

Farbmetrische Daten von Fernseh-Lichtfarben-System TLS00 für Helligkeit $L^*_N=00$ von Schwarz

System:
TLS00
Monitor:
CRT

Farbe	$r=olv^*_1$	$g=olv^*_2$	$b=olv^*_3$	$L^*_c=LAB^*_1c$	$a^*_c=LAB^*_2c$	$b^*_c=LAB^*_3c$	$C^*_{ab,c}=LAB^*_{rc}$	$h_{ab,c}$	$X_c=XYZ^*_1c$	$Y_c=XYZ^*_2c$	$Z_c=XYZ^*_3c$	x_c	y_c	$Y_c/88.59$
00 o00y	1.0	0.0	0.0	56.02	77.48	66.45	102.07	42	44.38	23.93	2.62	0.6257	0.3374	0.2701
01 o13y	1.0	0.125	0.0	56.02	77.28	66.41	101.9	42	44.31	23.93	2.62	0.6253	0.3377	0.2701
02 o25y	1.0	0.25	0.0	57.92	71.8	67.19	98.34	45	45.26	25.88	2.98	0.6106	0.3492	0.2921
03 o38y	1.0	0.375	0.0	62.19	59.5	69.13	91.21	51	47.4	30.62	3.86	0.5789	0.374	0.3457
04 o50y	1.0	0.5	0.0	67.72	44.39	72.09	84.66	61	50.6	37.59	5.13	0.5422	0.4028	0.4243
05 o63y	1.0	0.625	0.0	73.76	28.82	75.54	80.86	72	54.63	46.33	6.76	0.5071	0.4301	0.523
06 o75y	1.0	0.75	0.0	79.96	13.76	79.39	80.57	83	59.35	56.61	8.67	0.4762	0.4542	0.639
07 o88y	1.0	0.875	0.0	86.01	0.2	83.63	83.63	93	64.73	68.01	10.69	0.4513	0.4742	0.7677
08 y00l	1.0	1.0	0.0	91.93	-12.99	87.13	88.09	101	70.31	80.55	13.19	0.4286	0.491	0.9092
09 y13l	0.875	1.0	0.0	89.64	-24.0	84.58	87.92	108	61.01	75.52	12.63	0.409	0.5063	0.8525
10 y25l	0.75	1.0	0.0	87.47	-35.92	82.12	89.64	116	52.43	70.97	12.15	0.3868	0.5236	0.8011
11 y38l	0.625	1.0	0.0	85.44	-48.24	79.84	93.29	123	44.75	66.87	11.69	0.3629	0.5423	0.7548
12 y50l	0.5	1.0	0.0	83.56	-60.65	77.73	98.6	129	38.03	63.22	11.28	0.338	0.5618	0.7136
13 y63l	0.375	1.0	0.0	82.02	-72.3	75.94	104.86	134	32.65	60.33	10.97	0.3141	0.5804	0.681
14 y75l	0.25	1.0	0.0	80.88	-82.0	74.62	110.88	138	28.73	58.25	10.74	0.294	0.5961	0.6575
15 y88l	0.125	1.0	0.0	80.25	-87.72	73.89	114.7	140	26.61	57.12	10.61	0.2821	0.6054	0.6447
16 100c	0.0	1.0	0.0	80.17	-88.48	73.79	115.22	141	26.35	56.98	10.61	0.2805	0.6066	0.6432
17 113c	0.0	1.0	0.125	80.16	-88.43	73.41	114.94	141	26.35	56.96	10.73	0.2802	0.6057	0.643
18 125c	0.0	1.0	0.25	80.28	-86.86	66.19	109.21	143	26.86	57.18	13.53	0.2753	0.586	0.6454
19 138c	0.0	1.0	0.375	80.6	-83.19	51.95	98.09	148	28.12	57.74	20.48	0.2644	0.543	0.6518
20 150c	0.0	1.0	0.5	81.07	-77.87	35.94	85.77	155	30.02	58.59	30.89	0.2512	0.4903	0.6614
21 163c	0.0	1.0	0.625	81.71	-71.7	20.47	74.58	163	32.45	59.76	44.11	0.238	0.4384	0.6746
22 175c	0.0	1.0	0.75	82.43	-64.7	64.96	174	35.34	61.1	60.02	60.02	0.2259	0.3905	0.6897
23 188c	0.0	1.0	0.875	83.26	-57.4	-7.78	57.93	185	38.65	62.66	77.97	0.2156	0.3495	0.7073
24 c00v	0.0	1.0	1.0	84.22	-50.12	-20.03	53.99	198	42.33	64.49	97.58	0.2071	0.3155	0.728
25 c13v	0.0	0.875	1.0	77.24	-38.2	-30.47	48.88	214	36.57	51.93	95.19	0.1991	0.2827	0.5862
26 c25v	0.0	0.75	1.0	69.81	-24.32	-41.97	48.52	235	31.36	40.48	93.23	0.19	0.2452	0.4569
27 c38v	0.0	0.675	1.0	61.76	-8.13	-54.27	54.89	258	26.59	30.12	90.95	0.1801	0.204	0.34
28 c50v	0.0	0.5	1.0	53.37	10.02	-67.62	68.37	276	22.44	21.38	89.33	0.1685	0.1606	0.2414
29 c63v	0.0	0.375	1.0	44.84	31.31	-81.6	87.41	290	19.23	14.43	88.29	0.1577	0.1183	0.1628
30 c75v	0.0	0.25	1.0	37.25	52.3	-94.04	107.62	298	17.02	9.67	87.38	0.1492	0.0848	0.1092
31 c88v	0.0	0.125	1.0	33.58	63.94	-100.42	119.06	302	16.27	7.81	87.45	0.1459	0.07	0.0881
32 v00m	0.0	0.0	1.0	33.4	63.27	-100.11	118.43	302	16.02	7.72	86.57	0.1452	0.07	0.0872
33 v13m	0.125	0.0	1.0	33.76	63.95	-100.02	118.72	302	16.41	7.89	87.32	0.147	0.0707	0.0891
34 v25m	0.25	0.0	1.0	36.14	65.42	-95.89	116.09	304	18.57	9.08	87.28	0.1616	0.079	0.1025
35 v38m	0.375	0.0	1.0	39.92	68.67	-89.58	112.88	307	22.58	11.2	87.57	0.1861	0.0923	0.1264
36 v50m	0.5	0.0	1.0	44.48	73.01	-82.23	109.98	311	28.25	14.17	88.31	0.2161	0.1084	0.16
37 v63m	0.625	0.0	1.0	49.17	76.2	-73.8	106.09	315	34.63	17.73	87.83	0.247	0.1265	0.2002
38 v75m	0.75	0.0	1.0	54.0	80.89	-66.0	104.41	320	42.59	21.98	88.59	0.2781	0.1435	0.2481
39 v88m	0.875	0.0	1.0	58.64	85.03	-58.09	102.99	325	51.17	26.64	88.71	0.3073	0.16	0.3008
40 m00o	1.0	0.0	1.0	63.05	89.51	-50.96	103.0	330	60.56	31.65	89.38	0.3335	0.1743	0.3573
41 m13o	1.0	0.0	0.875	61.53	87.25	-38.83	95.5	336	56.9	29.85	69.87	0.3633	0.1906	0.337
42 m25o	1.0	0.0	0.75	60.16	84.9	-25.02	88.51	344	53.63	28.3	52.01	0.4004	0.2113	0.3194
43 m38o	1.0	0.0	0.675	58.9	82.72	-9.32	83.25	354	50.72	26.92	36.13	0.4458	0.2366	0.3038
44 m50o	1.0	0.0	0.5	57.81	85.9	4.99	86.05	4	50.15	25.76	24.88	0.4976	0.2556	0.2908
45 m63o	1.0	0.0	0.375	56.92	79.09	28.43	84.05	21	46.29	24.84	12.53	0.5533	0.2969	0.2804
46 m75o	1.0	0.0	0.25	56.33	78.02	50.44	92.9	35	45.03	24.24	5.58	0.6016	0.3239	0.2737
47 m88o	1.0	0.0	0.125	56.09	77.63	65.6	101.63	42	44.54	24.01	2.75	0.6247	0.3367	0.271
48 o00y	1.0	0.0	0.0	56.02	77.48	66.45	102.07	42	44.38	23.93	2.62	0.6257	0.3374	0.2701
49 n00w	0.0	0.0	0.0	0.46	-0.16	-0.09	0.2	0	0.04	0.05	0.06	0.2802	0.323	0.0006
50 n13w	0.125	0.125	0.125	2.38	4.33	1.25	4.5	18	0.36	0.26	0.2	0.435	0.3218	0.003
51 n25w	0.25	0.25	0.25	22.26	7.95	2.57	8.36	25	3.93	3.59	3.47	0.3576	0.3267	0.0405
52 n38w	0.375	0.375	0.375	39.92	6.15	1.68	6.38	33	11.48	11.2	11.57	0.3352	0.327	0.1264
53 n50w	0.5	0.5	0.5	54.11	5.42	0.6	5.45	37	22.13	22.08	23.68	0.326	0.3252	0.2492
54 n63w	0.625	0.625	0.625	66.29	5.06	-0.08	5.06	44	35.4	35.7	38.95	0.3217	0.3244	0.403
55 n75w	0.75	0.75	0.75	77.06	4.96	-1.02	5.06	43	50.91	51.63	57.3	0.3185	0.323	0.5828
56 n88w	0.875	0.875	0.875	86.67	5.13	-1.86	5.46	27	68.21	69.33	77.9	0.3166	0.3218	0.8286
57 n99w	1.0	1.0	1.0	95.41	4.95	-2.4	5.51	0	86.83	88.59	100.14	0.3151	0.3215	1.0

Siehe Original/Kopie: <http://web.me.com/klaus.richter/KG45/KG45LONP.PDF> / PS
 Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>

TUB-Registrierung: 20100601-KG45/KG45LONP.PDF / PS
 Anwendung für Messung von Drucker- oder Monitorsystemen
 TUB-Material: Code=rh4ta