

**Farbmetrische Daten von Fernseh-Lichtfarben-System TLS03 für Helligkeit  $L^*_N=03$  von Schwarz**

**System:  
 TLS03  
 Projektor:  
 LCD**

Farbe	$r=olv^*_1$	$g=olv^*_2$	$b=olv^*_3$	$L^*_c=LAB^*_1c$	$a^*_c=LAB^*_2c$	$b^*_c=LAB^*_3c$	$C^*_{ab,c}=LAB^*_rc$	$h_{ab,c}$	$X_c=XYZ^*_1c$	$Y_c=XYZ^*_2c$	$Z_c=XYZ^*_3c$	$x_c$	$y_c$	$Y_c/88.59$
00 o00y	1.0	0.0	0.0	37.1	58.78	56.51	81.54	44	18.1	9.59	0.52	0.6415	0.34	0.1083
01 o13y	1.0	0.125	0.0	37.41	58.02	56.42	80.93	44	18.21	9.76	0.57	0.6381	0.3421	0.1102
02 o25y	1.0	0.25	0.0	38.83	54.44	57.1	78.89	46	18.69	10.56	0.69	0.6243	0.3527	0.1192
03 o38y	1.0	0.375	0.0	42.44	42.95	59.04	73.01	54	19.48	12.78	0.99	0.5859	0.3844	0.1443
04 o50y	1.0	0.5	0.0	47.08	35.41	60.09	69.75	59	22.06	16.08	1.57	0.5556	0.4049	0.1815
05 o63y	1.0	0.625	0.0	54.15	21.26	63.91	67.35	71	25.77	22.11	2.53	0.5112	0.4387	0.2496
06 o75y	1.0	0.75	0.0	62.27	7.09	69.0	69.37	84	31.07	30.71	3.9	0.473	0.4676	0.3467
07 o88y	1.0	0.875	0.0	70.64	-4.64	74.95	75.09	93	38.14	41.66	5.61	0.4465	0.4878	0.4703
08 y00l	1.0	1.0	0.0	83.13	-16.8	84.65	86.31	101	52.58	62.4	8.73	0.425	0.5044	0.7044
09 y13l	0.875	1.0	0.0	81.19	-24.79	81.99	85.66	106	46.56	58.82	8.53	0.4087	0.5164	0.664
10 y25l	0.75	1.0	0.0	75.03	-33.74	75.48	82.68	114	35.07	48.33	7.36	0.3864	0.5325	0.5455
11 y38l	0.625	1.0	0.0	74.08	-40.51	73.85	85.23	118	31.97	46.83	7.36	0.3711	0.5435	0.5286
12 y50l	0.5	1.0	0.0	73.46	-45.58	72.79	84.89	122	29.89	45.87	7.36	0.3596	0.5519	0.5178
13 y63l	0.375	1.0	0.0	73.1	-48.78	72.15	87.1	124	28.66	45.32	7.36	0.3523	0.5572	0.5116
14 y75l	0.25	1.0	0.0	72.92	-50.49	71.84	87.82	125	28.02	45.04	7.36	0.3484	0.5601	0.5084
15 y88l	0.125	1.0	0.0	72.84	-51.23	71.69	88.12	125	27.75	44.92	7.36	0.3467	0.5613	0.5071
16 100c	0.0	1.0	0.0	72.83	-51.36	71.66	88.17	125	27.7	44.91	7.37	0.3464	0.5615	0.5069
17 113c	0.0	1.0	0.125	72.87	-51.21	70.8	87.39	126	27.78	44.96	7.62	0.3457	0.5595	0.5075
18 125c	0.0	1.0	0.25	72.97	-50.7	67.1	84.11	127	28.02	45.12	8.75	0.3422	0.551	0.5093
19 138c	0.0	1.0	0.375	73.17	-49.55	59.71	77.6	129	28.53	45.42	11.31	0.3346	0.5327	0.5127
20 150c	0.0	1.0	0.5	73.55	-47.47	48.77	68.07	134	29.49	46.01	16.04	0.3222	0.5026	0.5193
21 163c	0.0	1.0	0.625	74.19	-44.2	34.93	56.34	141	31.09	47.0	23.86	0.305	0.461	0.5305
22 175c	0.0	1.0	0.75	74.8	-39.66	19.62	44.25	153	33.08	47.96	34.95	0.2852	0.4135	0.5414
23 188c	0.0	1.0	0.875	76.29	-33.9	3.44	34.08	174	36.63	50.36	51.35	0.2648	0.364	0.5684
24 c00v	0.0	1.0	1.0	77.63	-27.89	-10.73	29.9	201	40.31	52.59	69.46	0.2483	0.3239	0.5936
25 c13v	0.0	0.875	1.0	69.94	-19.11	-22.45	29.5	230	32.97	40.66	67.61	0.2334	0.2879	0.459
26 c25v	0.0	0.75	1.0	60.8	-7.27	-36.62	37.35	260	25.8	29.02	65.75	0.214	0.2407	0.3276
27 c38v	0.0	0.675	1.0	51.55	6.79	-51.31	51.77	278	20.11	19.75	64.29	0.1931	0.1896	0.2229
28 c50v	0.0	0.5	1.0	43.25	21.59	-64.77	68.28	289	16.15	13.32	63.31	0.1741	0.1436	0.1504
29 c63v	0.0	0.375	1.0	36.87	34.74	-75.21	82.86	295	13.78	9.47	62.69	0.1603	0.1102	0.1069
30 c75v	0.0	0.25	1.0	32.68	44.51	-82.18	93.47	299	12.51	7.39	62.38	0.152	0.0898	0.0834
31 c88v	0.0	0.125	1.0	30.75	49.23	-85.41	98.59	300	11.99	6.55	62.29	0.1483	0.081	0.0739
32 v00m	0.0	0.0	1.0	30.28	50.46	-86.21	99.9	301	11.87	6.35	62.28	0.1475	0.0789	0.0717
33 v13m	0.125	0.0	1.0	30.52	50.74	-86.47	100.26	301	12.06	6.45	63.03	0.1479	0.0791	0.0728
34 v25m	0.25	0.0	1.0	30.67	50.94	-85.47	99.51	301	12.18	6.51	62.19	0.1506	0.0805	0.0735
35 v38m	0.375	0.0	1.0	31.48	51.96	-83.92	98.71	302	12.85	6.86	62.02	0.1572	0.0839	0.0774
36 v50m	0.5	0.0	1.0	33.02	53.8	-81.29	97.49	304	14.17	7.55	62.06	0.1691	0.0901	0.0852
37 v63m	0.625	0.0	1.0	35.31	56.61	-76.94	95.53	307	16.3	8.66	61.6	0.1883	0.1	0.0977
38 v75m	0.75	0.0	1.0	38.29	60.25	-71.06	93.17	310	19.37	10.25	60.77	0.2143	0.1134	0.1157
39 v88m	0.875	0.0	1.0	43.55	65.86	-65.4	92.82	315	25.51	13.53	64.62	0.2461	0.1305	0.1527
40 m00o	1.0	0.0	1.0	48.39	71.08	-60.47	93.32	320	32.22	17.11	68.65	0.2731	0.145	0.1931
41 m13o	1.0	0.0	0.875	44.49	67.04	-44.55	80.49	327	26.78	14.18	44.89	0.3119	0.1652	0.1601
42 m25o	1.0	0.0	0.75	41.5	64.08	-26.13	69.21	338	23.08	12.18	26.76	0.3721	0.1964	0.1375
43 m38o	1.0	0.0	0.675	39.82	62.04	-9.33	62.74	351	21.08	11.14	16.02	0.4369	0.231	0.1258
44 m50o	1.0	0.0	0.5	38.6	60.58	8.07	61.11	7	19.7	10.43	8.68	0.5077	0.2687	0.1177
45 m63o	1.0	0.0	0.375	37.83	59.69	25.05	64.73	23	18.87	9.99	4.23	0.5702	0.3019	0.1128
46 m75o	1.0	0.0	0.25	37.41	59.19	40.82	71.9	34	18.43	9.76	1.83	0.6138	0.3251	0.1102
47 m88o	1.0	0.0	0.125	37.23	58.94	53.08	79.32	42	18.24	9.67	0.78	0.6359	0.337	0.1091
48 o00y	1.0	0.0	0.0	37.1	58.78	56.51	81.54	44	18.1	9.59	0.52	0.6415	0.34	0.1083
49 n00w	0.0	0.0	0.0	2.5	-0.41	0.23	0.48	0	0.25	0.28	0.29	0.3103	0.3398	0.0031
50 n13w	0.125	0.125	0.125	4.56	-0.87	-0.48	1.01	238	0.46	0.5	0.58	0.2962	0.3263	0.0057
51 n25w	0.25	0.25	0.25	12.6	-1.6	-0.76	1.79	260	1.4	1.5	1.8	0.2978	0.3193	0.0169
52 n38w	0.375	0.375	0.375	23.36	-0.66	-1.79	1.92	264	3.67	3.91	4.6	0.3013	0.3208	0.0441
53 n50w	0.5	0.5	0.5	34.78	-0.55	-1.92	2.01	267	7.91	8.39	9.75	0.3037	0.322	0.0947
54 n63w	0.625	0.625	0.625	46.81	-0.46	-2.0	2.06	270	15.01	15.88	18.26	0.3054	0.323	0.1792
55 n75w	0.75	0.75	0.75	61.39	-0.67	-1.71	1.84	264	28.05	29.7	33.6	0.3071	0.3251	0.3352
56 n88w	0.875	0.875	0.875	80.86	-0.46	-0.03	0.48	324	55.14	58.21	63.43	0.3119	0.3293	0.6571
57 n99w	1.0	1.0	1.0	95.41	-0.54	-0.04	0.55	0	83.91	88.59	96.53	0.3119	0.3293	1.0

Siehe Original/Kopie: <http://web.me.com/klaus.richter/KG49/KG49LONP.PDF> / .PS  
 Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>

TUB-Registrierung: 20100601-KG49/KG49LONP.PDF / .PS  
 Anwendung für Messung von Drucker- oder Monitorsystemen  
 TUB-Material: Code=rh4ta