

Entrada i salida: Offset Reflective System ORS18a for relative CIELAB hue $h_{ab,a,rel} = h_{ab}/360 = 300/360 = 0.83$


$H^*_e = B25R_e$

Datos del dispositivo (d) o elemental (e) color:

HIC^*_e
código de tono para los colores
esta página:

$H^*_e = B25R_e$

triángulo claridad T^*



| ORS20a; datos adaptados CIELAB (a) | | | | | |
|------------------------------------|-------------|---------|---------|--------------|--------------|
| name | $L^*=L^*_a$ | a^*_a | b^*_a | $C^*_{ab,a}$ | $h^*_{ab,a}$ |
| $R_{e, Ma}$ | 45.6 | 72.2 | 34.4 | 80.0 | 25 |
| $Y_{e, Ma}$ | 83.6 | -3.6 | 90.4 | 90.4 | 92 |
| $G_{e, Ma}$ | 50.6 | -62.1 | 19.9 | 65.2 | 162 |
| $C_{e, Ma}$ | 55.0 | -36.2 | -27.2 | 45.3 | 216 |
| $B_{e, Ma}$ | 40.2 | 1.2 | -40.6 | 40.6 | 271 |
| $M_{e, Ma}$ | 31.1 | 47.7 | -29.1 | 55.9 | 328 |
| $N_{e, Ma}$ | 24.3 | 0.0 | 0.0 | 0.0 | 0 |
| $W_{e, Ma}$ | 95.6 | 0.0 | 0.0 | 0.0 | 0 |
| $R_{e, CIE}$ | 39.9 | 58.7 | 27.9 | 65.0 | 25 |
| $Y_{e, CIE}$ | 81.2 | -2.8 | 71.5 | 71.6 | 92 |
| $G_{e, CIE}$ | 52.2 | -42.4 | 13.6 | 44.5 | 162 |
| $B_{e, CIE}$ | 30.5 | 1.4 | -46.4 | 46.4 | 271 |

Los datos de color máximo (Ma):

$LabCh^*_{e, Ma}: 28\ 23\ -40\ 46\ 300$

$HIC^*_{e, Ma}: B25R_100_100_e$

$rgbic^*_{e, Ma}$:

0.0 0.1 1.0 1.0 1.0

triángulo claridad T^*

| ORS20a; datos adaptados CIELAB (a) | | | | | |
|------------------------------------|-------------|---------|---------|--------------|--------------|
| H^*_e | $L^*=L^*_a$ | a^*_a | b^*_a | $C^*_{ab,a}$ | $h^*_{ab,a}$ |
| $R00Y_100_100_e$ | 45.6 | 72.2 | 34.4 | 80.0 | 25 |
| $R25Y_100_100_e$ | 50.5 | 59.2 | 51.6 | 78.6 | 41 |
| $R50Y_100_100_e$ | 60.2 | 38.2 | 63.4 | 74.1 | 58 |
| $R75Y_100_100_e$ | 70.9 | 17.9 | 75.9 | 77.9 | 76 |
| $Y00G_100_100_e$ | 83.6 | -3.6 | 90.4 | 90.4 | 92 |
| $Y25G_100_100_e$ | 74.5 | -25.0 | 74.3 | 78.4 | 108 |
| $Y50G_100_100_e$ | 62.6 | -40.9 | 53.8 | 67.6 | 127 |
| $Y75G_100_100_e$ | 54.1 | -55.5 | 37.5 | 67.0 | 145 |
| $G00B_100_100_e$ | 50.6 | -62.1 | 19.9 | 65.2 | 162 |
| $G25B_100_100_e$ | 53.0 | -48.6 | -8.2 | 49.2 | 189 |
| $G50B_100_100_e$ | 55.0 | -36.2 | -27.2 | 45.3 | 216 |
| $G75B_100_100_e$ | 53.3 | -19.8 | -41.3 | 45.9 | 244 |
| $B00R_100_100_e$ | 40.2 | 1.2 | -40.6 | 40.6 | 271 |
| $B25R_100_100_e$ | 28.1 | 23.4 | -40.3 | 46.7 | 300 |
| $B50R_100_100_e$ | 31.1 | 47.7 | -29.1 | 55.9 | 328 |
| $B75R_100_100_e$ | 41.4 | 70.4 | -9.8 | 71.1 | 352 |

%Gama

$u^*_{rel} = 92$

%Regularidad

$g^*_{H,rel} = 57$

$g^*_{C,rel} = 58$

vea archivos semejantes: <http://130.149.60.45/~farbmetrik/RS26/RS26.HTM>
información técnica: <http://www.ps.bam.de> o <http://130.149.60.45/~farbmetrik>

TUB matrícula: 20130201-RS26/RS26LONP.PDF /.PS
aplicación para la medida salida en la impresión offset, separación cmy0 (CMY0)
TUB material: code=thad4a

