

<i>Cod.</i>	<i>i</i>	[X, Y, Z, x, y] ₁₀₀	[L*, a*, b*, C*, h _{ab} , a', b', c'] ₁₀₀	[Y, A, B, C _{AB} , h _{AB} , a, b, c _{AB}] ₁₀₀	[i _d , i _c , λ _d , λ _c] ₁₀₀	[X, Y, Z] ₈₉	[L*, a*, b*, C*, h _{ab}] ₈₉	[Y, A, B, C _{AB} , h _{AB}] ₈₉							
9900-W99N	80	0.7 0.8 0.9	0.312 0.329	7.0 0.0 0.0 0.0 227.8 0.215	-0.215 0.01	0.8 0.0 0.0 0.0 229.9 0.949	-0.435 0.01	16 36 481 583	0.7 0.7 0.8	6.2 0.0 0.0 0.0	0.0 0.0	227.8	0.7 0.0 0.0 0.0	0.0 0.0	229.7
9500-W95N	81	2.4 2.5 2.8	0.312 0.329	18.1 0.0 0.0 0.0 164.0 0.215	-0.214 0.01	2.5 0.0 0.0 0.0 160.6 0.949	-0.434 0.01	20 -1 504 504c	2.1 2.2 2.4	16.7 0.0 0.0 0.0	0.0 0.0	164.0	2.2 0.0 0.0 0.0	0.0 0.0	160.5
9000-W90N	82	4.2 4.4 4.8	0.313 0.329	25.0 0.0 0.0 0.0 329.0 0.215	-0.215 0.01	4.4 0.0 0.0 0.0 326.1 0.95	-0.434 0.01	-1 27 537c 537	3.7 3.9 4.2	23.3 0.0 0.0 0.0	0.0 0.0	329.0	3.9 0.0 0.0 0.0	0.0 0.0	326.2
8500-W85N	83	6.1 6.4 7.0	0.313 0.329	30.4 0.0 0.0 0.1 325.8 0.215	-0.215 0.01	6.4 0.0 0.0 0.0 322.4 0.95	-0.435 0.01	-1 28 542c 542	5.4 5.7 6.2	28.6 0.0 0.0 0.1	0.0 0.0	325.8	5.7 0.0 0.0 0.0	0.0 0.0	322.5
8000-W80N	84	8.1 8.6 9.3	0.313 0.329	35.1 0.0 0.0 0.0 318.5 0.215	-0.215 0.01	8.6 0.0 0.0 0.0 314.9 0.95	-0.434 0.01	-1 30 550c 550	7.2 7.6 8.3	33.1 0.0 0.0 0.0	0.0 0.0	318.5	7.6 0.0 0.0 0.0	0.0 0.0	315.0
7500-W75N	85	10.4 10.9 11.9	0.313 0.329	39.4 0.1 0.0 0.1 351.1 0.216	-0.214 0.01	10.9 0.0 0.0 0.0 350.1 0.95	-0.434 0.01	-1 19 497c 497	9.2 9.7 10.5	37.2 0.1 0.0 0.1	0.0 0.1	351.1	9.7 0.0 0.0 0.0	0.0 0.0	350.1
7000-W70N	86	12.8 13.4 14.6	0.313 0.329	43.4 0.1 0.0 0.1 331.0 0.215	-0.215 0.01	13.4 0.0 0.0 0.0 327.7 0.95	-0.434 0.01	-1 26 533c 533	11.3 11.9 12.9	41.0 0.1 0.0 0.1	0.0 0.1	331.0	11.9 0.0 0.0 0.0	0.0 0.0	327.8
6500-W65N	87	15.4 16.1 17.6	0.313 0.329	47.2 0.1 0.0 0.1 342.8 0.216	-0.215 0.01	16.1 0.0 0.0 0.0 340.6 0.95	-0.434 0.01	-1 21 506c 506	13.6 14.3 15.6	44.7 0.1 0.0 0.1	0.0 0.1	342.8	14.3 0.0 0.0 0.0	0.0 0.0	340.6
6000-W60N	88	18.2 19.1 20.8	0.313 0.329	50.8 0.1 0.0 0.1 334.8 0.216	-0.215 0.01	19.1 0.0 0.0 0.0 331.8 0.95	-0.435 0.01	-1 24 523c 523	16.1 16.9 18.5	48.2 0.1 0.0 0.1	0.0 0.1	334.8	16.9 0.0 0.0 0.0	0.0 0.0	331.8
5500-W55N	89	21.3 22.4 24.4	0.313 0.329	54.4 0.1 0.0 0.1 344.2 0.216	-0.214 0.01	22.4 0.0 0.0 0.0 342.1 0.95	-0.434 0.01	-1 20 504c 504	18.9 19.8 21.6	51.7 0.1 0.0 0.1	0.0 0.1	344.2	19.8 0.0 0.0 0.0	0.0 0.0	342.1
5000-W50N	90	24.7 26.0 28.3	0.313 0.329	58.0 0.1 0.0 0.2 339.5 0.216	-0.215 0.01	26.0 0.0 0.0 0.0 336.9 0.951	-0.435 0.01	-1 22 512c 512	21.9 23.0 25.0	55.1 0.1 0.0 0.1	0.0 0.1	339.5	23.0 0.0 0.0 0.0	0.0 0.0	336.9
4500-W45N	91	28.4 29.9 32.6	0.313 0.329	61.6 0.1 0.0 0.1 337.4 0.216	-0.215 0.01	29.9 0.0 0.0 0.0 334.6 0.951	-0.435 0.01	-1 23 517c 517	25.2 26.5 28.9	58.5 0.1 0.0 0.1	0.0 0.1	337.4	26.5 0.0 0.0 0.0	0.0 0.0	334.6
4000-W40N	92	32.6 34.3 37.3	0.313 0.329	65.2 0.1 0.0 0.1 340.2 0.216	-0.215 0.01	34.3 0.0 0.0 0.0 337.6 0.95	-0.434 0.01	-1 22 511c 511	28.9 30.4 33.1	62.0 0.1 0.0 0.1	0.0 0.1	340.2	30.4 0.0 0.0 0.0	0.0 0.0	337.6
3500-W35N	93	37.2 39.2 42.7	0.313 0.329	68.9 0.1 0.0 0.1 338.0 0.216	-0.215 0.01	39.2 0.0 0.0 0.0 335.2 0.95	-0.435 0.01	-1 23 515c 515	33.0 34.7 37.8	65.5 0.1 0.0 0.1	0.0 0.1	338.0	34.7 0.0 0.0 0.0	0.0 0.0	335.2
3000-W30N	94	42.4 44.7 48.6	0.313 0.329	72.7 0.1 0.0 0.2 341.0 0.216	-0.215 0.01	44.7 0.0 0.0 0.1 338.5 0.951	-0.434 0.01	-1 21 509c 509	37.6 39.6 43.1	69.2 0.1 0.0 0.2	0.0 0.2	341.0	39.6 0.0 0.0 0.0	0.0 0.0	338.5
2500-W25N	95	48.3 50.8 55.4	0.313 0.329	76.6 0.1 0.0 0.2 336.2 0.216	-0.215 0.01	50.8 0.1 0.0 0.1 333.2 0.95	-0.435 0.01	-1 24 520c 520	42.8 45.0 49.0	72.9 0.1 0.0 0.2	0.0 0.2	336.2	45.0 0.0 0.0 0.1	0.0 0.1	333.2
2000-W20N	96	55.0 57.9 63.1	0.313 0.329	80.7 0.2 0.0 0.2 338.8 0.216	-0.215 0.01	57.9 0.1 0.0 0.1 336.0 0.95	-0.435 0.01	-1 22 514c 514	48.8 51.3 55.9	76.9 0.1 0.0 0.2	0.0 0.2	338.8	51.3 0.1 0.0 0.1	0.0 0.1	336.0
1500-W15N	97	62.8 66.0 71.9	0.313 0.329	85.0 0.2 0.0 0.2 339.6 0.216	-0.215 0.01	66.0 0.1 0.0 0.1 336.9 0.95	-0.434 0.01	-1 22 512c 512	55.6 58.5 63.7	81.0 0.2 0.0 0.2	0.0 0.2	339.6	58.5 0.1 0.0 0.1	0.0 0.1	337.0
1000-W10N	98	71.7 75.5 82.2	0.313 0.329	89.6 0.2 0.0 0.2 338.8 0.216	-0.215 0.01	75.5 0.1 0.0 0.1 336.1 0.95	-0.435 0.01	-1 22 513c 513	63.6 66.9 72.8	85.4 0.2 0.0 0.2	0.0 0.2	338.8	66.9 0.1 0.0 0.1	0.0 0.1	336.1
0500-W05N	99	82.3 86.6 94.3	0.313 0.329	94.6 0.2 0.0 0.2 338.5 0.216	-0.215 0.01	86.6 0.1 0.0 0.1 335.7 0.95	-0.435 0.01	-1 22 514c 514	72.9 76.7 83.5	90.2 0.2 0.0 0.2	0.0 0.2	338.5	76.7 0.1 0.0 0.1	0.0 0.1	335.7
0000-W00N	100	94.9 99.9 108.8	0.313 0.329	100.0 0.2 0.0 0.2 338.2 0.216	-0.215 0.01	99.9 0.1 0.0 0.1 335.4 0.95	-0.435 0.01	-1 23 515c 515	84.1 88.5 96.4	95.4 0.2 0.0 0.2	0.0 0.2	338.2	88.5 0.1 0.0 0.1	0.0 0.1	335.4