

9stufige Grauskalierung zwischen $L^*_{0aN}=-40.0$ und $L^*_{0aW}=40.0$, $Y_{0ref}=1.8$, Normierung Grau U

$L^*_{0aN}=-39.9$, $L^*_{0aU}=0.0$, $L^*_{0aW}=40.0$, $Y_{0aN}=3.6$, $Y_{0aU}=18.0$, $Y_{0aW}=90.0$, $C_{0aY}=Y_{0aW}:Y_{0aN}=25.0$

$L^*_{taN}=-32.2$, $L^*_{taU}=0.0$, $L^*_{taW}=38.1$, $Y_{taN}=4.9$, $Y_{taU}=18.0$, $Y_{taW}=83.4$, $C_{taY}=Y_{taW}:Y_{taN}=17.0$

Regularitätsindex nach ISO/IEC 15775:2022, Anhang G für 5 und 9 Stufen

$g^* = 100 [\Delta L^*_{min}] / [\Delta L^*_{max}]$, $L^*_{TUBJND1} = 40 / \log(5) [\log(Y/Y_u)]$ mit $Y_u=18$

$g^*_5=100$, $g^*_9=100$

$g^*_5=76$, $g^*_9=72$

$g^*_5=98$, $g^*_9=94$

n0. i	angestrebte Ausgabe				reale Ausgabe					linearisierte Ausgabe	
	L^*_{0a}	L^*_{0r}	Y_{0a}	Y_{0r}	L^*_{ta}	ΔL^*_{ta}	L^*_{tr}	Y_{ta}	$(L^*_{tr})^{1/1.12}$	L^*_{la}	ΔL^*_{la}
9	40.0	1.0	90.0	1.0	38.1		1.0	83.4	1.0	38.1	
8	30.0	0.875	60.2	0.655	28.4	9.7	0.861	56.3	0.875	29.3	8.8
7	20.0	0.75	40.2	0.424	18.7	9.6	0.724	38.2	0.75	20.5	8.8
6	10.0	0.625	26.9	0.27	9.2	9.5	0.59	26.1	0.624	11.6	8.8
5	0.0	0.5	18.0	0.167	0.0	9.2	0.458	18.0	0.498	2.8	8.8
4	-9.9	0.375	12.0	0.098	-8.8	8.9	0.332	12.6	0.373	-5.9	8.8
3	-19.9	0.25	8.0	0.051	-17.3	8.4	0.212	8.9	0.25	-14.6	8.7
2	-29.9	0.125	5.4	0.021	-25.1	7.8	0.101	6.5	0.129	-23.1	8.6
1	-39.9	0.0	3.6	0.0	-32.2	7.1	0.0	4.9	0.0	-32.2	9.0

$\Delta L^*_{0a}=10.0$ (i=1,2,...,8)

Normierung: $Y_{taiU}=Y_{0aU} \frac{Y_{0ai}+Y_{0ref}}{Y_{0aU}+Y_{0ref}}$