

9stufige Grauskalierung zwischen $L^*_{0aN}=-40.0$ und $L^*_{0aW}=40.0$, $Y_{0ref}=90.0$, Normierung Grau U

$L^*_{0aN}=-39.9$, $L^*_{0aU}=0.0$, $L^*_{0aW}=40.0$, $Y_{0aN}=3.6$, $Y_{0aU}=18.0$, $Y_{0aW}=90.0$, $C_{0aY}=Y_{0aW}:Y_{0aN}=25.0$

$L^*_{taN}=-3.5$, $L^*_{taU}=0.0$, $L^*_{taW}=12.7$, $Y_{taN}=15.6$, $Y_{taU}=18.0$, $Y_{taW}=30.0$, $C_{taY}=Y_{taW}:Y_{taN}=1.9$

Regularitätsindex nach ISO/IEC 15775:2022, Anhang G für 5 und 9 Stufen

$g^* = 100 [\Delta L^*_{min}] / [\Delta L^*_{max}]$, $L^*_{TUBJND1} = 40 / \log(5) [\log(Y/Y_U)]$ mit $Y_U=18$

$g^*_5=100$, $g^*_9=100$

$g^*_5=14$, $g^*_9=10$

$g^*_5=71$, $g^*_9=54$

L* _{TUBJND1} n0. i	angestrebte Ausgabe				reale Ausgabe					linearisierte Ausgabe	
	L* _{0a}	L* _{0r}	Y _{0a}	Y _{0r}	L* _{ta}	ΔL^*_{ta}	L* _{tr}	Y _{ta}	$(L^*_{tr})^{1/2.06}$	L* _{la}	ΔL^*_{la}
○ 9	40.0	1.0	90.0	1.0	12.7		1.0	30.0	1.0	12.7	
● 8	30.0	0.875	60.2	0.655	8.2	4.5	0.723	25.0	0.854	10.3	2.4
● 7	20.0	0.75	40.2	0.424	4.6	3.5	0.505	21.7	0.718	8.1	2.2
● 6	10.0	0.625	26.9	0.27	2.0	2.7	0.34	19.5	0.592	6.1	2.0
● 5	0.0	0.5	18.0	0.167	0.0	2.0	0.219	18.0	0.478	4.2	1.8
● 4	-9.9	0.375	12.0	0.098	-1.3	1.4	0.132	17.0	0.374	2.5	1.7
● 3	-19.9	0.25	8.0	0.051	-2.3	1.0	0.071	16.3	0.277	0.9	1.6
● 2	-29.9	0.125	5.4	0.021	-3.0	0.7	0.029	15.9	0.179	-0.6	1.6
● 1	-39.9	0.0	3.6	0.0	-3.5	0.5	0.0	15.6	0.0	-3.5	2.9

$\Delta L^*_{0a}=10.0$

(i=1,2,...,8)

Normierung: $Y_{taiU}=Y_{0aU} \frac{Y_{0ai}+Y_{0ref}}{Y_{0aU}+Y_{0ref}}$