

**9stufige Grauskalierung zwischen  $L^*_{0aN}=-48.3$  und  $L^*_{0aW}=48.3$ ,  $Y_{0ref}=1.8$ , Normierung Weiß W**

$L^*_{0aN}=-48.3$ ,  $L^*_{0aU}=0.0$ ,  $L^*_{0aW}=48.4$ ,  $Y_{0aN}=2.6$ ,  $Y_{0aU}=18.0$ ,  $Y_{0aW}=126.0$ ,  $C_{0aY}=Y_{0aW}:Y_{0aN}=49.0$   
 $L^*_{taN}=-35.4$ ,  $L^*_{taU}=2.0$ ,  $L^*_{taW}=48.4$ ,  $Y_{taN}=4.3$ ,  $Y_{taU}=19.5$ ,  $Y_{taW}=126.0$ ,  $C_{taY}=Y_{taW}:Y_{taN}=29.2$

**Regularitätsindex nach ISO/IEC 15775:2022, Anhang G für 5 und 9 Stufen**

$g^* = 100 [\Delta L^*_{min}] / [\Delta L^*_{max}]$ ,  $L^*_{TUBJND1} = 40 / \log(5) [\log ( Y/Y_U )]$  mit  $Y_U=18$

$g^*_5=100$ ,  $g^*_9=100$

$g^*_5=71$ ,  $g^*_9=65$

$g^*_5=98$ ,  $g^*_9=94$

$L^*_{TUBJND1}$	n0. i	angestrebte Ausgabe				reale Ausgabe					linearisierte Ausgabe	
		$L^*_{0a}$	$L^*_{0r}$	$Y_{0a}$	$Y_{0r}$	$L^*_{ta}$	$\Delta L^*_{ta}$	$L^*_{tr}$	$Y_{ta}$	$(L^*_{tr})^{1/1.15}$	$L^*_{la}$	$\Delta L^*_{la}$
50	9	48.4	1.0	126.0	1.0	48.4		1.0	126.0	1.0	48.4	
	8						11.9					10.4
	7	36.3	0.875	77.4	0.607	36.5		0.858	78.1	0.876	38.0	
25	6	24.2	0.75	47.6	0.365	24.7		0.718	48.7	0.751	27.5	
	5						11.7					10.5
	4	12.1	0.625	29.3	0.216	13.2		0.581	30.6	0.625	16.9	
	3						11.5					10.6
0	2	0.0	0.5	18.0	0.125	2.0		0.447	19.5	0.499	6.3	
	1						11.2					10.6
	0	-12.0	0.375	11.1	0.069	-8.6		0.32	12.7	0.373	-4.2	
	9						10.7					10.5
-25	8	-24.1	0.25	6.8	0.034	-18.6		0.2	8.5	0.249	-14.5	
	7						10.0					10.4
	6	-36.2	0.125	4.2	0.013	-27.6		0.093	5.9	0.128	-24.7	
	5						9.0					10.1
	4	-48.3	0.0	2.6	0.0	-35.4		0.0	4.3	0.0	-35.4	
	3						7.8					10.7
-50	2											
	1											

$\Delta L^*_{0a}=12.1$  (i=1,2,...,8)

Normierung:  $Y_{taiW}=Y_{0aW} \frac{Y_{0ai}+Y_{0ref}}{Y_{0aW}+Y_{0ref}}$