

# 9stufige Grauskalierung zwischen $L^*_{0aN}=-50$ & $L^*_{0aW}=50.0$ , $Y_{0ref}=2$ , Normierung Weiß W

$L^*_{0aN}=-49.9$ ,  $L^*_{0aU}=0.0$ ,  $L^*_{0aW}=50.0$ ,  $Y_{0aN}=4.0$ ,  $Y_{0aU}=20.0$ ,  $Y_{0aW}=100.0$ ,  $C_{0aY}=Y_{0aW}:Y_{0aN}=25.0$   
 $L^*_{taN}=-37.9$ ,  $L^*_{taU}=2.3$ ,  $L^*_{taW}=50.0$ ,  $Y_{taN}=5.9$ ,  $Y_{taU}=21.6$ ,  $Y_{taW}=100.0$ ,  $C_{taY}=Y_{taW}:Y_{taN}=17.0$

## Regularitätsindex nach ISO/IEC 15775:2022, Anhang G für 5 und 9 Stufen

$g^* = 100 [\Delta L^*_{min}] / [\Delta L^*_{max}]$ ,  $L^*_{TUBLOG,Ua} = 50 / \log(5) [\log(Y/Y_u)]$  mit  $Y_u=20$

$g^*_5 = 100$ ,  $g^*_9 = 100$

$g^*_5 = 76$ ,  $g^*_9 = 72$

$g^*_5 = 98$ ,  $g^*_9 = 94$

L* <sub>TUBLOG,Ua</sub>	angestrebte Ausgabe				reale Ausgabe					linearisierte Ausgabe		
	n0. i	L* <sub>0a</sub>	L* <sub>0r</sub>	Y <sub>0a</sub>	Y <sub>0r</sub>	L* <sub>ta</sub>	$\Delta L^*_{ta}$	L* <sub>tr</sub>	Y <sub>ta</sub>	$(L^*_{tr})^{1/1.12}$	L* <sub>la</sub>	$\Delta L^*_{la}$
50	9	50.0	1.0	100.0	1.0	50.0		1.0	100.0	1.0	50.0	
	8	37.5	0.875	66.9	0.655	37.8	12.2	0.861	67.5	0.875	39.0	11.0
25	7	25.0	0.75	44.7	0.424	25.7	12.0	0.724	45.8	0.75	28.0	11.0
	6	12.5	0.625	29.9	0.27	13.9	11.8	0.59	31.3	0.624	16.9	11.1
0	5	0.0	0.5	20.0	0.167	2.3	11.5	0.458	21.6	0.498	5.8	11.0
	4	-12.4	0.375	13.4	0.098	-8.7	11.1	0.332	15.1	0.373	-5.0	11.0
	3	-24.9	0.25	8.9	0.051	-19.3	10.6	0.212	10.7	0.25	-15.9	10.8
-25	2	-37.4	0.125	6.0	0.021	-29.1	9.8	0.101	7.8	0.129	-26.6	10.7
	1	-49.9	0.0	4.0	0.0	-37.9	8.9	0.0	5.9	0.0	-37.9	11.3

$\Delta L^*_{0a} = 12.5$  (i=1,2,...,8)

Normierung:  $Y_{taiW} = Y_{0aW} \frac{Y_{0ai} + Y_{0ref}}{Y_{0aW} + Y_{0ref}}$